

# DT Panel Protector (B), 240 kA

## Data Solutions



The nVent ERICO DTX240 Series of Surge Protective Devices (SPD) North American and Worldwide standards compliance and provides premium protection against damaging transients and surge currents, particularly in IEC Class I & Class II and UL Type 1 & Type 2 locations. The innovative design allows for installation on the line or load of the service panels and removes the need for circuit breakers (B Version Only). With a 240 kA per phase surge rating, DTX240 is well suited for category C locations. It is typically used in applications including service entrances, distribution, branch panels, MCC, lighting panels, HVAC, and more. The nVent ERICO DTX240 also features a NEMA®-4X enclosure rating, making it suitable for outdoor applications.

### CERTIFICATIONS



### FEATURES

Excellent clamping and low UL voltage protection ratings

Features relay alarming for power/phase loss and status of SPD health

Design allows for easy removal and replacement of surge modules via lever assist

RS-485 Interface Standard

10 Year Warranty

### SPECIFICATIONS

| Catalog Number              | DTX240B12024<br>OSP | DTX240B12024<br>OHD | DTX240B208Y | DTX240B240D | DTX240B480D | DTX240B480Y |
|-----------------------------|---------------------|---------------------|-------------|-------------|-------------|-------------|
| Nominal System Voltage (Un) | 120/240 V           | 120/240 V           | 120/208 V   | 240 V       | 480 V       | 277/480 V   |

| CatalogNumber                           | DTX240B12024<br>OSP | DTX240B12024<br>OHD | DTX240B208Y         | DTX240B240D      | DTX240B480D      | DTX240B480Y         |
|-----------------------------------------|---------------------|---------------------|---------------------|------------------|------------------|---------------------|
| Distribution System                     | 1Ph 3W+G            | 3PhΔ 4W+G           | 3Ph 4W+G            | 3PhΔ 3W+G        | 3PhΔ 3W+G        | 3Ph 4W+G            |
| Max Continuous Operating Voltage (Uc)   | 150/300 VAC         | 150/275 VAC         | 150/300 VAC         | 275 VAC          | 510 VAC          | 350/700 VAC         |
| Nominal Discharge Current (In), UL      | 20kA 8/20 μs        | 20kA 8/20 μs        | 20kA 8/20 μs        | 20kA 8/20 μs     | 20kA 8/20 μs     | 20kA 8/20 μs        |
| Max Discharge Current (Imax), Per Phase | 240kA 8/20 μs       | 240kA 8/20 μs       | 240kA 8/20 μs       | 240kA 8/20 μs    | 240kA 8/20 μs    | 240kA 8/20 μs       |
| Impulse Current (Iimp), Per Mode        | 12.5kA 10/350 μs    | 12.5kA 10/350 μs    | 12.5kA 10/350 μs    | 12.5kA 10/350 μs | 12.5kA 10/350 μs | 12.5kA 10/350 μs    |
| Frequency                               | 50 – 60Hz           | 50 – 60Hz           | 50 – 60Hz           | 50 – 60Hz        | 50 – 60Hz        | 50 – 60Hz           |
| Voltage Protection Rating (VPR), L-G    | 700V                | 1200V               | 700V                | 1000V            | 1800V            | 1200V               |
| Voltage Protection Rating (VPR), L-L    | 1000V               | 1500V               | 1200V               | 1000V            | 1800V            | 1800V               |
| Voltage Protection Rating (VPR), L-N    | 600V                | 800V                | 700V                |                  |                  | 1200V               |
| Voltage Protection Rating (VPR), N-G    | 600V                | 1500V               | 700V                |                  |                  | 1200V               |
| Protection Modes                        | L-N<br>L-PE<br>N-PE | L-N<br>L-PE<br>N-PE | L-N<br>L-PE<br>N-PE | L-PE             | L-PE             | L-N<br>L-PE<br>N-PE |
| Short Circuit Current Rating (SCCR)     | 200kA               | 200kA               | 200kA               | 200kA            | 200kA            | 200kA               |
| Nominal Discharge Current (In), IEC     | 40kA 8/20 μs        | 40kA 8/20 μs        | 40kA 8/20 μs        | 40kA 8/20 μs     | 40kA 8/20 μs     | 40kA 8/20 μs        |

| CatalogNumber                               | DTX240B12024<br>OSP                                                                                                                           | DTX240B12024<br>OHD                                                                                                                           | DTX240B208Y                                                                                                                                   | DTX240B240D                                                                                                                                   | DTX240B480D                                                                                                                                   | DTX240B480Y                                                                                                                                   |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Voltage<br>Protection Level<br>(Up), IEC    | 1200 V @ 20 kA<br>3000 V @ 100<br>kA                                                                                                          | 1200 V @ 20 kA<br>3000 V @ 100<br>kA                                                                                                          | 1200 V @ 20 kA<br>3000 V @ 100<br>kA                                                                                                          | 1200 V @ 20 kA<br>3000 V @ 100<br>kA                                                                                                          | 1200 V @ 20 kA<br>3000 V @ 100<br>kA                                                                                                          | 1200 V @ 20 kA<br>3000 V @ 100<br>kA                                                                                                          |
| Short Circuit<br>Current Rating<br>(Isc cr) | 50kA                                                                                                                                          | 50kA                                                                                                                                          | 50kA                                                                                                                                          | 50kA                                                                                                                                          | 50kA                                                                                                                                          | 50kA                                                                                                                                          |
| Temperature                                 | -40 to 80°C                                                                                                                                   | -40 to 80°C                                                                                                                                   | -40 to 80°C                                                                                                                                   | -40 to 80°C                                                                                                                                   | -40 to 80°C                                                                                                                                   | -40 to 80°C                                                                                                                                   |
| Enclosure<br>Material                       | Metal with PC<br>Lid                                                                                                                          | Metal with PC<br>Lid                                                                                                                          | Metal with PC<br>Lid                                                                                                                          | Metal with PC<br>Lid                                                                                                                          | Metal with PC<br>Lid                                                                                                                          | Metal with PC<br>Lid                                                                                                                          |
| Enclosure<br>Rating                         | NEMA®-4X<br>UL® 50E Type 4                                                                                                                    | NEMA®-4X<br>UL® 50E Type 4                                                                                                                    | NEMA®-4X<br>UL® 50E Type 4                                                                                                                    | NEMA®-4X<br>UL® 50E Type 4                                                                                                                    | NEMA®-4X<br>UL® 50E Type 4                                                                                                                    | NEMA®-4X<br>UL® 50E Type 4                                                                                                                    |
| Lead Size                                   | 2.5 – 16mm <sup>2</sup>                                                                                                                       | 2.5 – 16mm <sup>2</sup>                                                                                                                       | 2.5 – 16mm <sup>2</sup>                                                                                                                       | 2.5 – 16mm <sup>2</sup>                                                                                                                       | 2.5 – 16mm <sup>2</sup>                                                                                                                       | 2.5 – 16mm <sup>2</sup>                                                                                                                       |
| Mounting                                    | 8 Screw<br>Locations                                                                                                                          | 8 Screw<br>Locations                                                                                                                          | 8 Screw<br>Locations                                                                                                                          | 8 Screw<br>Locations                                                                                                                          | 8 Screw<br>Locations                                                                                                                          | 8 Screw<br>Locations                                                                                                                          |
| Remote<br>Contact<br>Switching<br>Capacity  | 2.0 A @ 240 V                                                                                                                                 | 2.0 A @ 240 V                                                                                                                                 | 2.0 A @ 240 V                                                                                                                                 | 2.0 A @ 240 V                                                                                                                                 | 2.0 A @ 240 V                                                                                                                                 | 2.0 A @ 240 V                                                                                                                                 |
| Remote<br>Contacts                          | Yes (Form C)                                                                                                                                  | Yes (Form C)                                                                                                                                  | Yes (Form C)                                                                                                                                  | Yes (Form C)                                                                                                                                  | Yes (Form C)                                                                                                                                  | Yes (Form C)                                                                                                                                  |
| Status<br>Indication                        | Audible alarm<br>with silence<br>switch<br>Dual color<br>status LED<br>Mechanical flag<br>OLED Display<br>Surge/TOV<br>Counter,<br>Resettable | Audible alarm<br>with silence<br>switch<br>Dual color<br>status LED<br>Mechanical flag<br>OLED Display<br>Surge/TOV<br>Counter,<br>Resettable | Audible alarm<br>with silence<br>switch<br>Dual color<br>status LED<br>Mechanical flag<br>OLED Display<br>Surge/TOV<br>Counter,<br>Resettable | Audible alarm<br>with silence<br>switch<br>Dual color<br>status LED<br>Mechanical flag<br>OLED Display<br>Surge/TOV<br>Counter,<br>Resettable | Audible alarm<br>with silence<br>switch<br>Dual color<br>status LED<br>Mechanical flag<br>OLED Display<br>Surge/TOV<br>Counter,<br>Resettable | Audible alarm<br>with silence<br>switch<br>Dual color<br>status LED<br>Mechanical flag<br>OLED Display<br>Surge/TOV<br>Counter,<br>Resettable |
| Technology                                  | Hybrid<br>technology<br>utilizing thermal<br>disconnects                                                                                      | Hybrid<br>technology<br>utilizing thermal<br>disconnects                                                                                      | Hybrid<br>technology<br>utilizing thermal<br>disconnects                                                                                      | Hybrid<br>technology<br>utilizing thermal<br>disconnects                                                                                      | Hybrid<br>technology<br>utilizing thermal<br>disconnects                                                                                      | Hybrid<br>technology<br>utilizing thermal<br>disconnects                                                                                      |
| Certification<br>Details                    | CSA C22.2 No.<br>269.2<br>UL® 1449<br>Edition 5 Type<br>1/2, 20 kA<br>Mode                                                                    | CSA C22.2 No.<br>269.2<br>UL® 1449<br>Edition 5 Type<br>1/2, 20 kA<br>Mode                                                                    | CSA C22.2 No.<br>269.2<br>UL® 1449<br>Edition 5 Type<br>1/2, 20 kA<br>Mode                                                                    | CSA C22.2 No.<br>269.2<br>UL® 1449<br>Edition 5 Type<br>1/2, 20 kA<br>Mode                                                                    | CSA C22.2 No.<br>269.2<br>UL® 1449<br>Edition 5 Type<br>1/2, 20 kA<br>Mode                                                                    | CSA C22.2 No.<br>269.2<br>UL® 1449<br>Edition 5 Type<br>1/2, 20 kA<br>Mode                                                                    |

| CatalogNumber         | DTX240B12024<br>OSP                                                                                                                                                                                                            | DTX240B12024<br>OHD                                                                                                                                                                                                            | DTX240B208Y                                                                                                                                                                                                                    | DTX240B240D                                                                                                                                                                                                                    | DTX240B480D                                                                                                                                                                                                                    | DTX240B480Y                                                                                                                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Complies With         | ANSI®/IEEE®<br>C62.41.2-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.41.1-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.45-2002<br>Cat A, Cat B,<br>Cat C<br>EN 61643-11<br>Type 2<br>IEC® 61643-11<br>Class II | ANSI®/IEEE®<br>C62.41.2-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.41.1-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.45-2002<br>Cat A, Cat B,<br>Cat C<br>EN 61643-11<br>Type 2<br>IEC® 61643-11<br>Class II | ANSI®/IEEE®<br>C62.41.2-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.41.1-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.45-2002<br>Cat A, Cat B,<br>Cat C<br>EN 61643-11<br>Type 2<br>IEC® 61643-11<br>Class II | ANSI®/IEEE®<br>C62.41.2-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.41.1-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.45-2002<br>Cat A, Cat B,<br>Cat C<br>EN 61643-11<br>Type 2<br>IEC® 61643-11<br>Class II | ANSI®/IEEE®<br>C62.41.2-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.41.1-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.45-2002<br>Cat A, Cat B,<br>Cat C<br>EN 61643-11<br>Type 2<br>IEC® 61643-11<br>Class II | ANSI®/IEEE®<br>C62.41.2-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.41.1-2002<br>Cat A, Cat B,<br>Cat C<br>ANSI®/IEEE®<br>C62.45-2002<br>Cat A, Cat B,<br>Cat C<br>EN 61643-11<br>Type 2<br>IEC® 61643-11<br>Class II |
| Depth (D)             | 98.3mm                                                                                                                                                                                                                         | 98.3mm                                                                                                                                                                                                                         | 98.3mm                                                                                                                                                                                                                         | 98.3mm                                                                                                                                                                                                                         | 98.3mm                                                                                                                                                                                                                         | 98.3mm                                                                                                                                                                                                                         |
| Height (H)            | 330.7mm                                                                                                                                                                                                                        | 330.7mm                                                                                                                                                                                                                        | 330.7mm                                                                                                                                                                                                                        | 330.7mm                                                                                                                                                                                                                        | 330.7mm                                                                                                                                                                                                                        | 330.7mm                                                                                                                                                                                                                        |
| Width (W)             | 222.5mm                                                                                                                                                                                                                        | 222.5mm                                                                                                                                                                                                                        | 222.5mm                                                                                                                                                                                                                        | 222.5mm                                                                                                                                                                                                                        | 222.5mm                                                                                                                                                                                                                        | 222.5mm                                                                                                                                                                                                                        |
| Unit Weight           | 4.98kg                                                                                                                                                                                                                         | 5.38kg                                                                                                                                                                                                                         | 5.38kg                                                                                                                                                                                                                         | 5.18kg                                                                                                                                                                                                                         | 5.3kg                                                                                                                                                                                                                          | 5.45kg                                                                                                                                                                                                                         |
| Replacement<br>Module | DT2180DTXM                                                                                                                                                                                                                     | DT2180DTXM<br>DT2275DTXM                                                                                                                                                                                                       | DT2150DTXM                                                                                                                                                                                                                     | DT2275DTXM                                                                                                                                                                                                                     | DT2510DTXM                                                                                                                                                                                                                     | DT2350M                                                                                                                                                                                                                        |

## ADDITIONAL PRODUCT DETAILS

Optional Flush Plate and Side Mount Kits available: DTX240FP & DTX240SM

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE**