We connect and protect

Aisle Containment Battery Pack

Data Solutions



Battery pack: Prepared for integration into door box; 1200 charging cycles, supports opening for 8 doors, 14.7 VDC charging voltage via door plate, ambient temperature -15 °C ... +50 °C.

CERTIFICATIONS

RoHS COMPLIANT

FEATURES

- Ambient temperature -15 °C ... +50 °C
- Prepared for integration into door box
- 14.7 VDC charging voltage via door plate
- 1200 charging cycles
- Upports opening for 8 doors

SPECIFICATIONS

Table 1/1

Catalog Number	Works With	Package Quantity
60130-066	Sliding Containment Door	1

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.