

# Socket Strip, IEC C13

# **Power Utilities**



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with IEC C13 outlets.

#### **CERTIFICATIONS**



#### **FEATURES**

230 V, 10 A

Horizontal and vertical mounting

Socket strips can be rotated through all four directions (in 90° increments) during installation

Socket strips with IEC 60320-C13 sockets

Connecting cable 2 m, open end with ferrules

In accordance with IEC 60320

Mounting height 1 U

## **SPECIFICATIONS**

| Table 1/1         |             |            |       |       |          |              |  |  |  |
|-------------------|-------------|------------|-------|-------|----------|--------------|--|--|--|
| Catalog<br>Number | Socket Type | Voltage AC | Color | Depth | Length   | Product Type |  |  |  |
| 60110-290         | IEC C13     | 230 V      | Grey  | 44 mm | 438.5 mm | Socket Strip |  |  |  |

| CatalogNumber | Socket Type | Voltage AC | Color | Depth | Length   | Product Type |
|---------------|-------------|------------|-------|-------|----------|--------------|
| 60110-291     | IEC C13     | 230 V      | Grey  | 44 mm | 438.5 mm | Socket Strip |
| 60110-292     | IEC C13     | 230 V      | Grey  | 44 mm | 608.5 mm | Socket Strip |

### **ADDITIONAL PRODUCT DETAILS**

Please order bracket for vertical mounting separately.

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE