

Varistar CP Steel Door, Plain, Multi-Point Locking

Power Utilities

EMC and IP55 Steel Door with lever handle and 4-Point locking.

FEATURES

Lever handle with push button

Opening angle 180°

Steel door with 4-point locking for EMC applications

SPECIFICATIONS

Table 1/2							
Catalog Number	Rack Height	Height	Width	Color	Color Code	Locking Type	
21630-521	24 U	1200 mm	600 mm	Black Grey	RAL 7021	3-Point Locking	
21630-522	24 U	1200 mm	800 mm	Black Grey	RAL 7021	3-Point Locking	
21630-523	29 U	1400 mm	600 mm	Black Grey	RAL 7021	3-Point Locking	
21630-524	29 U	1400 mm	800 mm	Black Grey	RAL 7021	3-Point Locking	
21630-525	33 U	1600 mm	600 mm	Black Grey	RAL 7021	4-Point Locking	
21630-526	33 U	1600 mm	800 mm	Black Grey	RAL 7021	4-Point Locking	
21630-527	38 U	1800 mm	600 mm	Black Grey	RAL 7021	4-Point Locking	
21630-528	38 U	1800 mm	800 mm	Black Grey	RAL 7021	4-Point Locking	

CatalogNumber	Rack Height	Height	Width	Color	Color Code	Locking Type
21630-529	42 U	2000 mm	600 mm	Black Grey	RAL 7021	4-Point Locking
21630-530	42 U	2000 mm	800 mm	Black Grey	RAL 7021	4-Point Locking
21630-531	47 U	2200 mm	600 mm	Black Grey	RAL 7021	5-Point Locking
21630-532	47 U	2200 mm	800 mm	Black Grey	RAL 7021	5-Point Locking

Table 2/2							
Catalog Number	Product Type	Protection Rating					
21630-521	Cabinet Door	IP55					
21630-522	Cabinet Door	IP55					
21630-523	Cabinet Door	IP55					
21630-524	Cabinet Door	IP55					
21630-525	Cabinet Door	IP55					
21630-526	Cabinet Door	IP55					
21630-527	Cabinet Door	IP55					
21630-528	Cabinet Door	IP55					
21630-529	Cabinet Door	IP55					
21630-530	Cabinet Door	IP55					
21630-531	Cabinet Door	IP55					
21630-532	Cabinet Door	IP55					

ADDITIONAL PRODUCT DETAILS

Please purchase the grounding kit separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY TRACHTE ERICO HOFFMAN ILSCO SCHROFF