

# FC nVent ERIFLEX Flexibar to Busbar Clamp



## **CERTIFICATIONS**



## **FEATURES**

Connects nVent ERIFLEX Flexibar to copper busbar

Two plates complete with screws

Allows for excellent electrical contact

Installs quickly and easily

Ideal for on site modifications

RoHS compliant

## **SPECIFICATIONS**

Quality Class: 8.8
Clamping Capacity: 20mm


Finish: Electrogalvanized

Material: Steel

| Table 1/2         |                |              |                    |            |           |   |  |
|-------------------|----------------|--------------|--------------------|------------|-----------|---|--|
| Catalog<br>Number | Article Number | Busbar Width | Conductor<br>Width | Height (H) | Width (W) | A |  |

| FC50X24  | 553020 | 50 mm  | 20 - 24 mm | 75 mm  | 52 mm | 36 mm |
|----------|--------|--------|------------|--------|-------|-------|
| FC50X32  | 553030 | 50 mm  | 32 mm      | 75 mm  | 60 mm | 44 mm |
| FC50X40  | 553040 | 50 mm  | 40 mm      | 75 mm  | 68 mm | 52 mm |
| FC80X24  | 553050 | 80 mm  | 20 - 24 mm | 105 mm | 52 mm | 36 mm |
| FC80X32  | 553060 | 80 mm  | 32 mm      | 105 mm | 60 mm | 44 mm |
| FC80X50  | 553070 | 80 mm  | 50 mm      | 105 mm | 78 mm | 62 mm |
| FC100X32 | 568700 | 100 mm | 32 mm      | 125 mm | 60 mm | 44 mm |
| FC120X32 | 568730 | 120 mm | 32 mm      | 145 mm | 60 mm | 44 mm |

| Table 2/2      |                |        |                     |             |             |  |  |
|----------------|----------------|--------|---------------------|-------------|-------------|--|--|
| Catalog Number | Article Number | В      | Screw Diameter (Sc) | Torque (TQ) | Unit Weight |  |  |
| FC50X24        | 553020         | 60 mm  | 8                   | 10 N·m      | 0.32 kg     |  |  |
| FC50X32        | 553030         | 60 mm  | 8                   | 10 N·m      | 0.36 kg     |  |  |
| FC50X40        | 553040         | 60 mm  | 8                   | 10 N·m      | 0.41 kg     |  |  |
| FC80X24        | 553050         | 90 mm  | 8                   | 10 N·m      | 0.43 kg     |  |  |
| FC80X32        | 553060         | 90 mm  | 8                   | 10 N·m      | 0.49 kg     |  |  |
| FC80X50        | 553070         | 90 mm  | 8                   | 10 N·m      | 0.64 kg     |  |  |
| FC100X32       | 568700         | 110 mm | 8                   | 10 N·m      | 0.67 kg     |  |  |
| FC120X32       | 568730         | 130 mm | 8                   | 10 N·m      | 0.76 kg     |  |  |



## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America** 

+1.800.753.9221 Option 1 - Customer Care Option 2 - Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404 **APAC** 

Shanghai: + 86 21 2412 1618/19 Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY TRACHTE ERICO HOFFMAN ILSCO SCHROFF**