

# **CPCI PlusIO Backplane**



CompactPCI PlusIO combines the legacy CompactPCI and the new, high speed CompactPCI Serial Technology on one backplane. The CompactPCI PlusIO system slot addesses both, the parallel PCI bus as well as the CompactPCI Serial slots with PCIe, USB, Ethernet and S-ATA.

## **CERTIFICATIONS**





## **FEATURES**

In accordance with: PICMG 2.0 R3.0 CompactPCI Core Specification, PICMG 2.1 R2.0 Hot-Swap Specification, PICMG 2.9 R1.0 System Management Bus Specification, PICMG 2.10 R1.0 Keying Specification, PICMG 2.30 R1.0 CompactPCI PlusIO specification, PICMG CompactPCI Serial (CPCI-S.0 R1.0) specification

System slot in accordance with PICMG 2.30, 32-bit CPCI bus on P1, PCIe, S-ATA, USB & Ethernet on P2

CompactPCI peripheral slots, 32 bit with rear I/O on P2

Rear I/O on the CompactPCI Serial slots available on request

CompactPCI Serial peripheral slots with PCIe x1, S-ATA and USB

Full-mesh Ethernet on system slot and 2 CompactPCI Serial slots, supports 1000Base-T and 10GBase-T

V(I/O) can be set to 3.3 V or 5 V (preset to 5 V)

# **SPECIFICATIONS**

| Table 1/3         |              |                 |             |   |             |            |
|-------------------|--------------|-----------------|-------------|---|-------------|------------|
| Catalog<br>Number | Product Type | Number of Slots | Rack Height | Backplane<br>Type                             | System Slot | Slot Width |
| 23007-602         | Backplane    | 5               | 3U          | CompactPCI<br>PlusIO,<br>CompactPCI<br>Serial | Middle      | 4HP        |

| CatalogNumber | Product Type | Number of Slots | Rack Height | BackplaneType                                 | System Slot | Slot Width |
|---------------|--------------|-----------------|-------------|---|-------------|------------|
| 23007-601     | Backplane    | 8               | 3U          | CompactPCI<br>PlusIO,<br>CompactPCI<br>Serial | Middle      | 4HP        |

| Table 2/3         |             |                      |                                 |                              |         |                     |
|-------------------|-------------|----------------------|---------------------------------|------------------------------|---------|---------------------|
| Catalog<br>Number | Voltage I/O | Connector<br>Type    | Power<br>Connector<br>Type      | Utility<br>Connector<br>Type | Width   | Package<br>Quantity |
| 23007-602         | 5V          | HM 2.0, AirMax<br>VS | Power Bugs for<br>M4 Cable Lugs | MicroMatch, 8-<br>pin        | 102.2mm | 1                   |
| 23007-601         | 5V          | HM 2.0, AirMax<br>VS | Power Bugs for<br>M4 Cable Lugs | MicroMatch, 8-               | 161.3mm | 1                   |

| Table 3/3      |            |  |  |
|----------------|------------|--|--|
| Catalog Number | Quick Ship |  |  |
| 23007-602      | No         |  |  |
| 23007-601      | No         |  |  |

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

# Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

## Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: nvent.com/schroff

## Middle East & India

Dubai, United Arab **Emirates** +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF** TRACHTE