

## Partial Height Swing Frames, SFCP



A partial height swing frame for 19" equipment that provides additional mounting space for such equipment, as well as rear access to the fitted components and equipment once opened.

## **FEATURES**

Description: Partial height swing frame for 19"-components allowing left or right hand opening. Can be used in wall mounted, steel enclosures, and floor standing, combinable and compact, steel enclosures. Rigid S-shaped frame profile equipped with 19" hole pattern in front and back. Zinc plated frame for direct earthing of the mounted components. Standard opening angle 125°-155°. Mounting in wall mounted, steel enclosures requires the SFBP transversal support in combination with the AVB. Mounting in floor standing steel combinable enclosures requires the SFBP transversal support.

Lock: 1 double-bit 3 mm lock.

Material: 2 mm zinc plated steel.

Pack quantity: 1 swing frame with hinges.

Mounting requirements: Mounting in wall mounted, steel enclosures requires the SFBP transversal support in combination with the AVB. Mounting in floor standing steel combinable enclosures requires the SFBP transversal support. Adjustable in depth in combination with CLPK profiles.

## **SPECIFICATIONS**

Thickness: 2mm

Material: Mild SteelFinish: Zinc Plated

Table 1/1						
Catalog Number	Height	Width	Depth	Enclosure Material	Load Rating	Rack Height
SFCP106	600mm	496mm	60mm	Mild Steel	500N	10U
SFCP156	800mm	696mm	60mm	Mild Steel	500N	15U
SFCP246	1200mm	1096mm	60mm	Mild Steel	500N	24U
SFCP126	800mm	696mm	60mm	Mild Steel	500N	12U
SFCP196	1000mm	896mm	60mm	Mild Steel	500N	19U
SFCP036	600mm	496mm	60mm	Mild Steel	150N	3U
SFCP066	600mm	496mm	60mm	Mild Steel	300N	6U

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE