

915 Series, Limiter Module

nVent RAYCHEM HTC-915-LIM/TX are a range of temperature limiters for the HTC-915 controller, providing protection against over-temperature of heat tracing cables in T-class limited areas. Available as a base unit for use with the HTC-915-CONT (lock out temperature can be programmed from the front panel) or in versions with preprogrammed lock out temperatures for T1, T2, T3, T4 and T5 classified areas.

FEATURES

Easy to install

Smart limiter when used in combination with the HTC-915 controller

SPECIFICATIONS

Operating Temperature: $20 - 450 \, ^{\circ}\text{C}$ Width: $45 \, \text{mm}$ Height: $77 \, \text{mm}$ Voltage Rating: $100 - 250 \, \text{V}$ Depth: $105 \, \text{mm}$

Contact Type: Breaker Contact

Table 1/1		
Catalog Number	Item Name	Lock Out Temperature
10275-003	HTC-915-LIM	
10275-004	HTC-915-LIM/T1	450 °C
10275-005	HTC-915-LIM/T2	300 °C
10275-006	HTC-915-LIM/T3	200 °C
10275-007	HTC-915-LIM/T4	135 °C
10275-008	HTC-915-LIM/T5	100 °C

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com