

Ground Rod Clamp with Prefabricated Pigtail



FEATURES

Prefabricated assembly including grounding clamp with pigtail

Fast and simple installation requires only a hammer

SPECIFICATIONS

Material: Copper

Insulation: Green and Yellow Insulated Cable

| Table 1/1 | | | | | | |
|-------------------|----------------|------------------------------------|------------|----------------|--------------------------------|-------------|
| Catalog Number | Article Number | Ground Rod Diameter, Nominal | Length (L) | Pigtail Length | Conductor Size | Unit Weight |
| EPT1225300 | 158610 | 1/2" | 70mm | 300mm | 25 mm ² Stranded | 0.5 kg |
| EPT1450350 | 158290 | 5/8" | 75mm | 350mm | 50 mm ² Stranded | 0.5 kg |
| EPT1425350 | 158675 | 5/8" | 75mm | 350mm | 25 mm ² Stranded | 0.5 kg |



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

Netherlands: +31 800-0200135 France:

+33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404 APAC

Shanghai: + 86 21 2412 1618/19 Sydney:

+61 2 9751 8500

TRACHTE



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF