

GM-TA



nVent RAYCHEM GM-TA is an electronic thermostat for small roof de-icing applications, gutter lengths up to 30 m. Available with outdoor junction box (GM-TA-OUTDOOR-BOX) and spare ambient sensor (GM-TA-AS).

FEATURES

Simple and fast to install: DIN rail mounted in panel

Energy saving: ambient control, double temperature set points

Safe: adjustable post heating time

Reliable during long life: 6 year extended product warranty available

SPECIFICATIONS

Table 1/3							
Catalog Number	Item Name	Supply Voltage	Output Relay	Alarm Relay	Terminal Size	Hysteresis/Diff erential	
1244-017783	GM-TA	207 – 253 V	16 A @ 230 VAC	Switch-Over Contact, Potential-Free, max 8 A @ 230 VAC	2.5 mm²	+/-1K	

Table 2/3							
Catalog Number	Item Name	Adjustment Range	Adjustment Range, Frost Protection	Material	Mounting	IP Rating	
1244-017783	GM-TA	−25 to −5 °C	0 - 6 °C	ABS	DIN Rail	IP20	

Table 3/3							
Catalog Number	Item Name	Ambient Temperature	Sensor Type	Sensor Cable Diameter			

1244-017783 GM-TA -25 to 40 °C NTC, 2KΩ @ 25°C 4 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com