


Aluminum Structure Grounding Stud, Top Angled Plate



FEATURES

Bimetallic assembly of aluminum and copper

For grounding new and existing aluminum structures: i.e., masts, signal bridges, cases and bungalows

For connection (nVent ERICO Cadweld recommended) to ground rod or ground network/mesh

SPECIFICATIONS


Table 1/2

Catalog Number	Material	Length 1 (L1)	Length 2 (L2)	Length 3 (L3)	Width (W)	Height (H)
SBB855F1G36	Aluminum, Copper	50.8 mm	92 mm	1220mm	50.8 mm	38.1 mm

Table 2/2

Catalog Number	Thickness (T)	Conductor Size
SBB855F1G36	6.35 mm	#6 Solid

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE