

# **Cast Junction Box for MI Cables**

nVent RAYCHEM cast metal junction boxes for use with mineral insulated (MI) heating units in non-hazardous and hazardous Class I Div 1 and Div 2 areas. NPT threaded entries for direct connection of MI cold lead cable glands. Terminal strip included for conductor sizes up to 6 AWG. Typically used for power or splice connection of heating units.

### **FEATURES**

Simple to install

Reliable during long life: 10 year product warranty available, maintenance free

Explosion proof, dust proof, wet location options available

Terminal strip with voltage ratings up to 600 V and current rating up to 65 A

Maximum 5 x 3/4" NPT tapered entries depending on model selected

3/4" NPT entries can be converted to 1/2" NPT with reducer bushings

Various mounting options are available

#### **SPECIFICATIONS**

**NEMA Rating:** 4X

Material: Aluminium

**Area Classification:** Non-Hazardous; Hazardous

Cover Attachment: Screwed

**Mounting:** Surface Mounted/Recessed Mounted

Cover Included: Yes
Sealable: Yes

| Table 1/2         |           |             |                              |                         |          |        |  |
|-------------------|-----------|-------------|------------------------------|-------------------------|----------|--------|--|
| Catalog<br>Number | Item Name | Max Voltage | Finish                       | Cable Entry<br>Quantity | AWG Size | Height |  |
| 232377-000        | RMI-JB3   | 500 V       | Silver Powder<br>Epoxy Paint | 3                       | #18 - #6 | 133 mm |  |
| PT-JB             |           | 600 V       | Untreated                    | 3                       | #18 - #6 | 95 mm  |  |
| XMI-JB            |           | 600 V       | Powder Coated                | 5                       | #18 - #6 | 114 mm |  |

| Table 2/2      |           |        |        |  |  |  |
|----------------|-----------|--------|--------|--|--|--|
| Catalog Number | Item Name | Width  | Depth  |  |  |  |
| 232377-000     | RMI-JB3   | 122 mm | 81 mm  |  |  |  |
| PT-JB          |           | 95 mm  | 127 mm |  |  |  |
| XMI-JB         |           | 114 mm | 60 mm  |  |  |  |

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa Tel +32.16.213.511

Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com