

nVent CADDY Cat HP J-Hook with T-Grid Clip

Data Solutions



CERTIFICATIONS





FEATURES

No installation tools required for basic clip

Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic

Provides superior fill capacity and load rating over most other non-continuous cable support alternatives

Rounded edges on J-Hooks provide proper bend radius support for high performance data cables

Cost effective alternative to expensive cable tray

Complies with EN 50174-2

Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569

SPECIFICATIONS

Table 1/3						
Catalog Number	Article Number	E-Number	Material	Finish	Diameter (Ø)	Area

CAT16HPTS	181089	1340707	Steel, Spring Steel	nVent CADDY Armour, Pregalvanized	25mm	690mm²
-----------	--------	---------	------------------------	---	------	--------

Table 2/3						
Catalog Number	Article Number	E-Number	Cable Capacity, Cat 5e	Cable Capacity, Cat 6	Cable Capacity, Cat 6A	A
CAT16HPTS	181089	1340707	20	15	10	65mm

Table 3/3						
Catalog Number Article Number		E-Number	Static Load			
CAT16HPTS	181089	1340707	270N			


ADDITIONAL PRODUCT DETAILS

Additional support wire required per NEC® 300.11.

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.

Cable capacity is calculated based on a 70% fill rate.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**