


# Novastar Raised Top Cover

## Power Utilities



Raised top cover for better ventilation and heat escape.  
Novastar raised top cover is robust and not dismountable from the outside.

## CERTIFICATIONS



## FEATURES

Raised Top cover (31 mm) with all-round air gap of 10 mm

Top cover attached from the inside (no screws on the outside)

Suitable for placing heavy parts on the top cover

Incl. grounding

Robust version, load-carrying capacity 50 kg

## SPECIFICATIONS

Table 1/1

| Catalog Number | Depth   | Color      | Color Code | Product Type           | Type   | Width  |
|----------------|---------|------------|------------|------------------------|--------|--------|
| 25230-039      | 500 mm  | Black Grey | RAL 7021   | Cabinet/Rack Top Cover | Raised | 553 mm |
| 25230-142      | 1000 mm | Black Grey | RAL 7021   | Cabinet/Rack Top Cover | Raised | 553 mm |

| CatalogNumber | Depth  | Color      | Color Code | Product Type              | Type   | Width  |
|---------------|--------|------------|------------|---------------------------|--------|--------|
| 25230-037     | 800 mm | Black Grey | RAL 7021   | Cabinet/Rack<br>Top Cover | Raised | 553 mm |
| 25230-141     | 900 mm | Black Grey | RAL 7021   | Cabinet/Rack<br>Top Cover | Raised | 553 mm |
| 25230-038     | 600 mm | Black Grey | RAL 7021   | Cabinet/Rack<br>Top Cover | Raised | 553 mm |

## ADDITIONAL PRODUCT DETAILS

Please order lifting eye separately if required.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE**