

Push-In Insert



FEATURES

For installation of lights, cable trunkings, electrical boxes, smoke detectors directly against concrete surfaces

Tool-free push-in installation after hole has been drilled into the concrete


Halogen free

UV-stabilized

SPECIFICATIONS

Table 1/2							
Catalog Number	Article Number	Material	Temperature	Drill Hole Depth	Hole Size (HS)	A	
SCDSN30	800055	Nylon	-10 to 85 °C	30mm	6 mm	7 mm Max	

Table 2/2						
Catalog Number	Article Number	Static Load				
SCDSN30	800055	200N				



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE

