

EuropacPRO 19" Subrack Kit for Railway, Retrofit Shielding, EN 50155

Power Utilities



Subrack for Railway applications, conform to EN50155 standard, non-shielded.

CERTIFICATIONS



FEATURES

Shock and vibration tested to EN 50155, part 12.2.11

The 19" bracket is firmly fixed to the side panel (tox-cold welded) and is especially suited for high mechanical stresses (vibration resistance)

Modifications such as cutouts, different finishes or dimensions available

IP 20, in accordance with IEC 60529

The double 19" screwing position adds to additionally safety (NFF standard)

Supplied as space-saving flat-pack

SPECIFICATIONS

Table 1/3						
Catalog Number	Rack Height	Depth	Package Quantity	For Mounting	Board Depth	EMC Gasket Type

21500-077	3 U	235 mm	1	Backplane	220 mm	Textile
21500-078	6 U	235 mm	1	Backplane	220 mm	Textile

Table 2/3						
Catalog Number	Shock and Vibration Tolerance	Handle Included	Mounting	Complies With	EMC Shielding	Product Type
21500-077	5 g (force)	Yes	Rack	IEC 60297-3- 103, EN 50155 part 12.2.11	No	Subrack/Chassi
21500-078	5 g (force)	Yes	Rack	IEC 60297-3- 103, EN 50155 part 12.2.11	No	Subrack/Chassi

Table 3/3					
Catalog Number	Rack Width	Static Load			
21500-077	84 HP	15 kgf			
21500-078	84 HP	15 kgf			

ADDITIONAL PRODUCT DETAILS

Test reports are available online.

Individual configuration: broad range of variants in height, width and depth; guide rails for a wide variety of applications; interior options; accessories and mounting material.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**