

Hydraulic Busbar Cutter



CERTIFICATIONS



FEATURES

Works with copper or aluminium busbar

Produces a flat and clean cut edge

Clear plastic shields allow for visual inspection of cutting position

Strong mechanical assembly

Replacement blade available

Easy access for blade maintenance

RoHS compliant

SPECIFICATIONS

Table 1/2

Catalog Number	Article Number	Busbar Width	Busbar Thickness	Depth (D)	Height (H)	Width (W)
HYDR-BB-CUT	545690	125 mm Max	12.7 mm Max	240mm	395 mm	286 mm

Table 2/2


Catalog Number	Article Number	Unit Weight
----------------	----------------	-------------

HYDR-BB-CUT	545690	41 kg
-------------	--------	-------

ADDITIONAL PRODUCT DETAILS

Do not use to cut nVent ERIFLEX Flexibar.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE