

# Elbow 45-Degree Lay-in Hinged-Cover



Lay-in Hinged-Cover 45-Degree Elbows are used for continuous wireway runs with 45-degree turns. Because sections of lay-in wireway can be mounted with covers oriented in any direction, three different 45-degree elbows are available. Proper selection allows the user to maintain the same access and thereby preserve the lay-in feature for right-angle installations.

#### **INDUSTRY STANDARDS**

Certified by Canadian Standards Association.

### **FEATURES**

Lay-in Hinged-Cover 45-Degree Elbows are used for continuous wireway runs with 45-degree turns

Because sections of lay-in wireway can be mounted with covers oriented in any direction, three different 45-degree elbows are available

Proper selection allows the user to maintain the same access and thereby preserve the lay-in feature for right-angle installations

## **SPECIFICATIONS**

ANSI 61 **Color Code:** 

Finish: Galvanized; Powder Coated

Color: Gray Mild Steel Material:

Table 1/1						
Catalog Number	Article Number	Туре	Height	Width	Thickness	Sealing Plate Type
F126LE45A	18840	Elbow	305mm	152mm	1.9mm	Flat
F22LE45A	18140	Elbow	64mm	64mm	1.9mm	Flat
F22LE45B	18150	Elbow	64mm	64mm	1.9mm	Flat
F22LE45C	18160	Elbow	64mm	64mm	1.9mm	Flat
F44LE45A	18370	Elbow	102mm	102mm	1.9mm	Flat
F44LE45B	18380	Elbow	102mm	102mm	1.9mm	Flat
F44LE45C	18390	Elbow	102mm	102mm	1.9mm	Flat
F66LE45A	18610	Elbow	152mm	152mm	1.9mm	Flat
F66LE45B	18620	Elbow	152mm	152mm	1.9mm	Flat
F66LE45C	18630	Elbow	152mm	152mm	1.9mm	Flat
F88LE45A	19260	Elbow	203mm	203mm	1.9mm	Flat
F88LE45B	19270	Elbow	203mm	203mm	1.9mm	Flat
F88LE45C	19280	Elbow	203mm	203mm	1.9mm	Flat

## ADDITIONAL PRODUCT DETAILS

Each sealing plate also includes one gasket and one set of screws to join sections.

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN TRACHTE ILSCO** SCHROFF