

# Modular Jumper Cable Clear, Plastic Connectors



nVent RAYCHEM TraceTek TT-MJC-XX-PC is a range of fixed length modular jumper connectors used to bridge between sections of sensing cable or leader cables, provided with plastic connectors.

## FEATURES

Simple and fast to install: small, lightweight

Easy to design

Reliable during long life: 10 year product warranty available, maintenance free

## SPECIFICATIONS

<b>Core Quantity:</b>	4
<b>Outer Diameter:</b>	4.2 mm
<b>Conductor Size:</b>	18 AWG
<b>Color:</b>	Clear Jacket
<b>Core Identification:</b>	Colour
<b>Conductor Material:</b>	Copper
<b>Outer Sheath Material:</b>	ECTFE
<b>Insulation Material:</b>	Fluorinated Ethylene Propylene (FEP)
<b>Connector Material:</b>	Plastic

Table 1/1

Catalog Number	Item Name	Length
050533-000	TT-MJC-30M/100FT-PC	30 m
740923-000	TT-MJC-1M/3FT-PC	1 m

Catalog Number	Item Name	Length
783027-000	TT-MJC-15M/50FT-PC	15 m
813259-000	TT-MJC-7M/25FT-PC	7.5 m
836567-000	TT-MJC-3M/10FT-PC	3 m

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

Tel +1.800.545.6258  
Fax +1.800.527.5703  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Europe, Middle East, Africa

Tel +32.16.213.511  
Fax +32.16.213.604  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Asia Pacific

Tel +86.21.2412.1688  
Fax +86.21.5426.3167  
[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

### Latin America

Tel +1.713.868.4800  
Fax +1.713.868.2333  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

Our powerful portfolio of brands:

**RAYCHEM PYROTENAX TRACER NUHEAT**