

# TT1100-OHP Water Sensing Cable for Suspended Piping, Modular



nVent RAYCHEM TraceTek TT1100-XX-OHP is a range of fixed length water detecting cable intended for use on the bottom side of suspended or rack mounted pipe. The outer layer of the sensor cable is designed to act like a wick so that even small leaks are drawn into contact with the cable to assure detection. TT1100-OHP is also very useful in dirty areas where contamination can cause problems.

# **FEATURES**

Advanced technology: synthetic fiber braid, designed to wick water along the cable even when the water leak is dripping from a single small pin hole or crack

Simple and fast to install: strap directly to the pipe, eliminate drip trays

Easy to design: rapid drying, so that once the leak is located and repaired it will be ready for re-use

Distributed leak detection and location over a wide range of areas

# **SPECIFICATIONS**

Outer Diameter: 8.2 mm

Max Operating Temperature: 80 °C

**Detection Method:** Raychem Conductive-Polymer Technology

Model: Sensing Cable

**Detection:** Water

Table 1/1			
Catalog Number	Item Name	Length	
P000000809	TT1100-OHP-15M-PC	15 m	
P000000811	TT1100-OHP-3M-PC	3 m	
P000000808	TT1100-OHP-30M-PC	30 m	

Catalog Number	Item Name	Length
P000000806	TT1100-OHP-100M-PC	100 m
P000000807	TT1100-OHP-50M-PC	50 m
P000001378	TT1100-OHP-5M-PC	5 m
P000000810	TT1100-OHP-7.5M-PC	7.5 m
P000000812	TT1100-OHP-1M-PC	1 m

# **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

# North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific** 

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com