


EuropacPRO Cover Plate for Bolting to Side Panel



A cover plate is used for electromagnetic shielding or as mechanical protection. The cover can be screwed onto the side panel.

CERTIFICATIONS



FEATURES

For variable positioning of horizontal rails e.g. for PCBs with standard formats

Perforation degree 58%

Suitable for use with all horizontal rails

SPECIFICATIONS

Material:AluminumProduct Type:Cover PlateProduct Family:EuropacPROFinish:PassivatedType:PerforatedWorks With:Subracks

Table 1/1										
Catalog Number	Rack Width	Depth	Package Quantity	Package Unit	Torque	Quick Ship				

42HP					
	175mm	2	Pair	2.1N·m	No
42HP	295mm	2	Pair	2.1N·m	No
42HP	275mm	2	Pair		No
42HP	235mm	2	Pair	2.1N·m	No
63HP	175mm	2	Pair	2.1N·m	No
42HP	277.75mm	2	Pair	2.1N·m	No
63HP	235mm	2	Pair	2.1N·m	No
84HP	175mm	2	Pair	2.1N·m	No
63HP	275mm	2	Pair		No
63HP	295mm	2	Pair	2.1N·m	No
84HP	235mm	2	Pair	2.1N·m	No
84HP	275mm	2	Pair		No
84HP	277.75mm	2	Pair	2.1N·m	No
84HP	295mm	2	Pair	2.1N·m	No
84HP	355mm	2	Pair	2.1N·m	No
84HP	415mm	2	Pair	2.1N·m	No
84HP	475mm	2	Pair	2.1N·m	No
	42HP 42HP 53HP 53HP 53HP 53HP 53HP 53HP 53HP 53	275mm 42HP 235mm 42HP 235mm 53HP 175mm 53HP 277.75mm 53HP 275mm 53HP 275mm 53HP 275mm 53HP 275mm 53HP 295mm 54HP 277.75mm 54HP 275mm 54HP 275mm 54HP 275mm 54HP 275mm	275mm 2 42HP 235mm 2 42HP 235mm 2 53HP 175mm 2 53HP 277.75mm 2 53HP 235mm 2 53HP 275mm 2 53HP 275mm 2 53HP 275mm 2 53HP 295mm 2 53HP 295mm 2 53HP 235mm 2 53HP 275mm 2	42HP 275mm 2 Pair 42HP 235mm 2 Pair 53HP 175mm 2 Pair 42HP 277.75mm 2 Pair 53HP 235mm 2 Pair 53HP 275mm 2 Pair 53HP 295mm 2 Pair 34HP 235mm 2 Pair 34HP 275mm 2 Pair 34HP 277.75mm 2 Pair 34HP 295mm 2 Pair 34HP 295mm 2 Pair 34HP 355mm 2 Pair 34HP 355mm 2 Pair 34HP 415mm 2 Pair	42HP 275mm 2 Pair 2.1N·m 42HP 235mm 2 Pair 2.1N·m 53HP 175mm 2 Pair 2.1N·m 42HP 277.75mm 2 Pair 2.1N·m 53HP 235mm 2 Pair 2.1N·m 33HP 175mm 2 Pair 2.1N·m 53HP 295mm 2 Pair 2.1N·m 34HP 235mm 2 Pair 2.1N·m 34HP 275mm 2 Pair 2.1N·m 34HP 277.75mm 2 Pair 2.1N·m 34HP 295mm 2 Pair 2.1N·m 34HP 355mm 2 Pair 2.1N·m 34HP 355mm 2 Pair 2.1N·m

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE