

Speedway Cable Ladder Inside Riser, 45°



CERTIFICATIONS



FEATURES

Creates a 45° inside riser elevation change for cable tray

Provides optimal support for high-performance low voltage and data cables

Innovative SPEEDLOK integrated coupling system

Safety edge protects cables during installation

Slotted side channel, eliminating field drilling for cut-to-length applications

IEC 61537 load rating and earthing compliant

Responsive design and layout services, including seismic

SPECIFICATIONS

Finish: Hot-Dip Galvanized


Material: Steel

Table 1/2						
Catalog Number	Article Number	Width (W)	Angle (a)	A	В	С

CL110X150IR45 HD	840300	150 mm	45 °	286 mm	193 mm	290 mm
CL110X300IR45 HD	840310	300 mm	45 °	286 mm	193 mm	290 mm
CL110X450IR45 HD	840320	450 mm	45 °	286 mm	193 mm	290 mm
CL110X600IR45 HD	840330	600 mm	45 °	286 mm	193 mm	290 mm
CL110X750IR45 HD	840340	750 mm	45 °	286 mm	193 mm	290 mm
CL110X900IR45 HD	840350	900 mm	45 °	286 mm	193 mm	290 mm

Table 2/2						
Catalog Number	Article Number	D				
CL110X150IR45HD	840300	80 mm				
CL110X300IR45HD	840310	80 mm				
CL110X450IR45HD	840320	80 mm				
CL110X600IR45HD	840330	80 mm				
CL110X750IR45HD	840340	80 mm				
CL110X900IR45HD	840350	80 mm				





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 - Customer Care Option 2 - Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE

