

SBS-T2 Control Panel for Pipe Freeze Protection

nVent RAYCHEM SBS-T2 control panel provides an integrated solution for nVent RAYCHEM self-regulating heating cables in pipe freeze protection applications. Offering multi-circuits, each with line sensing control and integrated electrical protection. A 400 VAC (3 phase) supply is required.

FEATURES

Simple and fast connection of multiple circuits, directly into a single panel

High capacity, with up to 3 maximum circuit lengths connected into the panel

Fully integrated system: all connections, circuit protection and safety devices integrated into the panel

Energy saving: with line sensing control

Reliable, complete system from one manufacturer and specifically designed for freeze protection of sprinkler systems

Reliable during long life: 6 year extended product warranty available, maintenance free

SPECIFICATIONS

| Table 1/2 | | | | | | | | | |
|----------------------|-----------------------------|---------------------------------------|--------|--------|---------------------|-----------|--|--|--|
| Catalog Number | Circuit Breaker Quantity | Circuit Breaker Quantity, 30 mA | Depth | Height | Housing Material | IP Rating | | | |
| 6012-T2-2S- 9X16A | 3 | 3 | 200 mm | 800 mm | Steel | IP55 | | | |

| Table 2/2 | | | | | | | | | | |
|----------------------|----------|-------------------------------|--------------|----------------|-------------------------------|--------|--|--|--|--|
| Catalog Number | Lockable | Main Switch Current Rating | Mounting | Phase Quantity | Pole Quantity, Main Switch | Width | | | | |
| 6012-T2-2S- 9X16A | Yes | 63 A | Wall Mounted | 3 | 3 | 600 mm | | | | |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper

installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com **Latin America**

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com