

Telescopic Slide, Universal, Heavy Load, 2 U



Telescopic slides with 10 to 100 kg load capacity, > 100% extension length and with lateral mounting capability on 19". Robust telescopic sliding-rails - suitable for the installation of 19 inch chassis are suitable for mounting server enclosures from our product portfolio. Due to the extremely robust construction and high load capacity, the telescopic slides can also be used with very heavy housings.

CERTIFICATIONS



FEATURES

Static load-carrying capacity per pair 72 - 100 kg

Lateral mounting on the 19" uprights (19" plane remains free for fixing the extension/drawer)

End stop damped

Extension length > 100 %

Rail width k = 19.1 mm, max. installation width of extension/drawer w = 411 mm

SPECIFICATIONS

Material: Steel

Product Type: Telescopic Slide
Finish: Zinc Plated

Table 1/1								
Catalog Number	Length	Package Quantity	Static Load	Туре	Quick Ship			
20110-190	300mm	2	77kg	Universal	No			

Catalog Number	Length	Package Quantity	Static Load	Туре	Quick Ship
20110-191	350mm	2	83kg	Universal	No
20110-192	400mm	2	88kg	Universal	No
20110-193	450mm	2	94kg	Universal	No
20110-194	500mm	2	100kg	Universal	No
20110-195	550mm	2	94kg	Universal	No
20110-196	600mm	2	88kg	Universal	No
20110-198	700mm	2	72kg	Universal	No

ADDITIONAL PRODUCT DETAILS

To mount on 19" plane please order assembly kit separately.

Universal telescopic rails can also be fitted without additional components in non-standard applications, thus also in other than 19" cabinets.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misused misused products are observed to completely follow nVent's instructions and warnings may equal to the completely follow nVent's instructions and warnings may equal to the completely follow nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions are completely follows nVent's instructions and the completely follows nVent's instructions are completely follows nVent's not completely follows nVent's number of the completely follows nVent's number of the completely follows n

North America

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE