

# Cable to Web of Rail Mold Only, Signal

## **Data Solutions**



### **FEATURES**

Replacement mold designed for the installation of track circuits and jumper bonds to the neutral axis

### **SPECIFICATIONS**

Rail Type: 85 lb to 141 lb T-Rail Sections

**Material:** Graphite

Table 1/1							
Catalog Number	Bond Terminal Style	Conductor Size	Conductor Outer Diameter, Nominal	Welder Style	Orientation		
SBB200CLH	1" Tab	3/16" Bondstrand	4.76mm	TB5, T21	Left Hand		
SBB200CRH	1" Tab	3/16" Bondstrand	4.76mm	TB5, T21	Right Hand		
SBW3150BLH	1" Tab	3/16" Bondstrand	4.76mm	TB5	Left Hand		
SBW3150BRH	1" Tab	3/16" Bondstrand	4.76mm	TB5	Right Hand		
SBB200YLH	1" Tab	16 mm² Concentric	5.18mm	T21, TB5	Left Hand		

Catalog Number	Bond Terminal Style	Conductor Size	Conductor Outer Diameter, Nominal	Welder Style	Orientation
SBB200YRH	1" Tab	16 mm <sup>2</sup> Concentric	5.18mm	T21, TB5	Right Hand
SBB200XRH	1" Tab	25 mm² Stranded	6.6mm	TB5, T21	Right Hand
SBB200PLH	1" Tab	35 mm² Stranded	7.75mm	TB5, T21	Left Hand
SBB200PRH	1" Tab	35 mm² Stranded	7.75mm	TB5, T21	Right Hand
SBWW6LH	Field-made	50 mm² Solid	8mm	T21	Left Hand
SBWW6RH	Field-made	50 mm² Solid	8mm	T21	Right Hand

### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN TRACHTE ILSCO SCHROFF**