

# T-Series Horizontal Transition Sleeve, Top Fill



The top fill horizontal T-Series sleeve has vent holes to reduce air entrapment and help ensure proper filling of the sleeve.

## **FEATURES**

Designed to connect horizontal reinforcing bars and angular reinforcing bars up to 45 degrees

Used to splice different diameter bars

Works with saw cut, flame cut and sheared bars

Can be visually inspected after installation

Available with extended sleeve lengths

### **SPECIFICATIONS**

Finish: Plain

**Sleeve:** Standard Length

Material: Steel 100% U.S. Domestic Content: Yes

| Table 1/2         |                       |                |                       |                    |                    |               |  |  |
|-------------------|-----------------------|----------------|-----------------------|--------------------|--------------------|---------------|--|--|
| Catalog<br>Number | Rebar Size,<br>Metric | Rebar Size, US | Rebar Size,<br>Canada | Diameter 1<br>(Ø1) | Diameter 2<br>(Ø2) | Length 1 (L1) |  |  |
| RBT1418101HA      | 57 mm, 43 mm          | #18, #14       | 55M, 45M              | 86 mm              | 67 mm              | 165 mm        |  |  |
| RBT1114101HA      | 43 mm, 36 mm          | #14, #11       | 45M, 35M              | 70 mm              | 52 mm              | 152 mm        |  |  |

| Table 2/2      |               |               |             |  |  |  |  |
|----------------|---------------|---------------|-------------|--|--|--|--|
| Catalog Number | Length 2 (L2) | Length 3 (L3) | Unit Weight |  |  |  |  |

| RBT1418101HA | 76 mm | 26mm | 3.55 kg |
|--------------|-------|------|---------|
| RBT1114101HA | 76 mm | 26mm | 2.19 kg |

Designed to Meet: AASHTO;ABNT NBR 8548:1984;ACI 318 Type 1 (125% Specified Yield);ACI 318 Type 2 (Specified


Tensile);ACI 349;ACI 359;AS3600

### ADDITIONAL PRODUCT DETAILS

Prior to installation, please read and understand all of the detailed instructions and safety notices provided in the nVent LENTON Cadweld Rebar Splicing System Instruction Manual.

Sizes not shown may be available by special order. Contact your nVent LENTON representative for more information.

### **DIAGRAMS**



### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### **North America**

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

# Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

#### Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

## APAC

Shanghai: + 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

©2025 nVent, All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE