

Universal Busbar Support



CERTIFICATIONS







FEATURES

Universal fixing system

Installs quickly and easily

Extremely robust construction

Adjustable arms for easy mounting

Halogen free insulators

SPECIFICATIONS

Max Working Voltage, IEC (Ui): 1000;1500

Material: Steel; Glass Fibre Reinforced Polyamide

Complies With: IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)

Flammability Rating: UL® 94V-0 Working Temperature: -40 to 130 $^{\circ}$ C


Table 1/3						
Catalog Number	Article Number	E-Number	Typical Application Current Rating	Busbars per Phase	Busbar Width	Busbar Thickness


UBS4-5T	551020	2674420	3500 A	1 - 4	30 - 125 mm	5 mm
UBS2-10T	551080		3600 A	1 - 2	30 - 120 mm	10 mm

Table 2/3						
Catalog Number	Article Number	E-Number	Width (W)	A	В	С
UBS4-5T	551020	2674420	375 - 575 mm	350 - 550 mm	176 mm	307 mm
UBS2-10T	551080		375 - 575 mm	350 - 550 mm	176 mm	307 mm

Table 3/3						
Catalog Number	Article Number	E-Number	D			
UBS4-5T	551020	2674420	110 mm			
UBS2-10T	551080		110 mm			

DIAGRAMS





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE