

No Pry Clip



CERTIFICATIONS











FEATURES

Eliminates prying effect on fasteners and anchors

Meets CEN/TS 17551:2021 requirements for Seismic Sway Bracing

SPECIFICATIONS

Finish: Electrogalvanized

Material: Steel


Table 1/1					
Catalog Number	Article Number	Brace Size	Hole Size (HS)	UL Listed Load	
CSBNPC38	402528	#12, #18, #36	11 mm	8490N	
CSBNPC12	402208	#12, #18, #36	14 mm	8490N	

ADDITIONAL PRODUCT DETAILS

Brace member is not included.

UL Loads				
Part Number	Brace Member	Load Rating		
	CSB12CBL	1859 N		
CSBNPC38	CSB18CBL	3434 N		
	CSB36CBL	8496 N		
	CSB12CBL	1859 N		
CSBNPC12	CSB18CBL	3434 N		
	CSB36CBL	8496 N		

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO S

SCHROFF

TRACHTE

