

# **RayClic Connection Kit**

## **Data Solutions**



nVent RAYCHEM RayClic connection system is a simple, fast and reliable set of connection kits developed for select nVent RAYCHEM XL-Trace, IceStop and HWAT self-regulating heating cables. No heat guns or wire stripping are needed, because insulation displacement technology is used to make the electrical connection.

#### **FEATURES**

Simple, fast, intuitive connection: no wire stripping or special tools needed

Lower total installed system cost, due to reduced installation time: cold applied, no heat guns or special tools needed

Reliable during long life: 10 year extended product warranty available, maintenance free

Cold applied, no heat guns needed, no special tools

#### **SPECIFICATIONS**

**Max Exposure Temperature:** 65°C

Connection Type: Cold Applied

Color: Grey

Table 1/1						
Catalog Number	Article Number	Model	Voltage Rating	<b>Current Rating</b>		
441524-000	RAYCLIC-T-02	T-Branch	240V	20A		
001013-000	RAYCLIC-X-02	X-Branch	240V	20A		
364855-000	RAYCLIC-S-02	Heating Cable/Heating Cable	240V	20A		
716976-000	RAYCLIC-PS-02	Power Connection to Two Heating Cables	240V	20A		

Catalog Number	Article Number	Model	Voltage Rating	<b>Current Rating</b>
235422-000	RAYCLIC-CE-02	Power Connection to One Heating Cable	240V	20A
636284-000	RAYCLIC-PT-02	Power Connection and T-Branch	240V	20A
559871-000	RAYCLIC-S-03	Heating Cable/Heating Cable	120 – 277V	30A
014023-000	RAYCLIC-T-03	T-Branch	120 – 277V	30A
233053-000	RAYCLIC-PC-03	Power Connection to One Heating Cable	120 – 277V	30A

### **ADDITIONAL PRODUCT DETAILS**

For proper design and installation of a RayClic connection system, use the appropriate product design guide and the installation instructions included with the connection kit.

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE