

# Fixing Tape



nVent RAYCHEM GT-66 is a glass installation tape to attach trace heating cables to pipes. For use on stainless steel, or when installation temperatures drop below 40 °F / 5 C°, use GS-54 fixing tape. AT-180 / ATE-180 aluminum tape is used to attach heating cables and thermostat sensors to pipes and tanks.

## FEATURES

Simple and fast to install

## SPECIFICATIONS

Table 1/1

| Catalog Number | Item Name             | Width   | Length | Suitable for Stainless Steel Pipes |
|----------------|-----------------------|---------|--------|------------------------------------|
| 846243-000     | ATE-180               | 63.5 mm | 55 m   | Yes                                |
| 158139-000     | TAPES-AT-180-ALUMINUM | 63.5 mm | 55 m   | Yes                                |
| C77221-000     | GS-54                 | 12.7 mm | 16.5 m | Yes                                |
| C77220-000     | GT-66                 | 12.7 mm | 20 m   | No                                 |

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

Tel +1.800.545.6258

Fax +1.800.527.5703

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

**Europe, Middle East,  
Africa**

Tel +32.16.213.511

Fax +32.16.213.604

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

**Asia Pacific**

Tel +86.21.2412.1688

Fax +86.21.5426.3167

[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

**Latin America**

Tel +1.713.868.4800

Fax +1.713.868.2333

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

Our powerful portfolio of brands:

**RAYCHEM   PYROTENAX   TRACER   NUHEAT**