


Horizontal Rail Rear, Type AB for Rear I/O Board Guides, 63 HP

CATALOG NUMBER

34561-563



Combinations of horizontal rails and side panels

Δ^{H} = can be combined, Δ^{H} = combination not recommended

RAILTYPE	RAILTYPE	RAILTYPE	RAILTYPE	RAILTYPE	RAILTYPE
RAILTYPE 1		-	-	-	RAILTYPE 1 suggests
		+	RAILTYPE 1 blocks the RAILTYPE 2	RAILTYPE 1 blocks the RAILTYPE 2 and the RAILTYPE 2 blocks the RAILTYPE 1	+
RAILTYPE 2		+	RAILTYPE 2 blocks the RAILTYPE 3	-	-
		+	RAILTYPE 2 blocks the RAILTYPE 4	-	-
RAILTYPE 3		RAILTYPE 3			
RAILTYPE 4		RAILTYPE 4			
RAILTYPE 5		RAILTYPE 5			
RAILTYPE 6		RAILTYPE 6			

RAILTYPE 1: 100 mm, RAILTYPE 2: 150 mm, RAILTYPE 3: 200 mm, RAILTYPE 4: 250 mm, RAILTYPE 5: 300 mm, RAILTYPE 6: 350 mm, RAILTYPE 7: 400 mm, RAILTYPE 8: 450 mm, RAILTYPE 9: 500 mm, RAILTYPE 10: 550 mm, RAILTYPE 11: 600 mm, RAILTYPE 12: 650 mm, RAILTYPE 13: 700 mm, RAILTYPE 14: 750 mm, RAILTYPE 15: 800 mm, RAILTYPE 16: 850 mm, RAILTYPE 17: 900 mm, RAILTYPE 18: 950 mm, RAILTYPE 19: 1000 mm, RAILTYPE 20: 1050 mm.

Aluminum extrusion horizontal rail of the type AB (AB = support), for rear I/O card guides, with an anodized surface and conductive contact surface. Suitable for RatiopacPRO/-AIR and EuropacPRO/-rugged).

CERTIFICATIONS



FEATURES

For CompactPCI in the area of rear I/O

For 2×3 U expansion, 2 horizontal rails of type AB are required

Aluminum extrusion, anodized surface, conductive contact surface, without HP markings

PRODUCT ATTRIBUTES

Rack Width: 63HP

Package Quantity: 1

Finish: Anodized

Length: 325.12mm

Material: Aluminum

Product Family: EuropacPRO; RatiopacPRO; RatiopacPRO AIR; CompacPRO; PropacPRO

Product Type: Horizontal Rail

Type: Type AB

Works With: Subracks; Cases

ADDITIONAL PRODUCT DETAILS

Delivery is in standard pack multiples. Pricing is per individual item.

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE