

nVent ERIFLEX FleXbus Transformer Cover IP2X for 1 Conductor per Phase



CERTIFICATIONS









FEATURES

Input/output for neutral/ground conductor

Resistance to solvent and hydrocarbon splashes

Installs quickly and easily

UV resistance


SPECIFICATIONS


Table 1/2								
Catalog Number	Article Number	Material	Working Temperature	Length (L)	Width (W)	Depth (D)		
FLEXCOVIP2XO NE	508160	Polyvinylchlorid e	-40 to 140 °C	465mm	182 mm	126mm		

Table 2/2					
Catalog Number	Article Number	Unit Weight			

FLEXCOVIP2XONE 508160		0.53 kg
-----------------------	--	---------

DIAGRAMS





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France:

+33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE