

# **Elexant 650c-Modbus Control Unit**



The nVent RAYCHEM Elexant 650c-Modbus controller is designed for operation with the nVent RAYCHEM heating cables for roof and gutter de-icing and surface snow melting applications.

## **FEATURES**

Intuitive set-up and programming of the unit with a 4,3" colour touch screen

Flexible temperature control of roof & gutter de-icing and surface snow melting systems

Controls 2 independent heating circuits

Alarm relay with change over contact to signal power, temperature or communication problems

Ambient temperature monitoring with high and low temperature alarm

Offsite configurable - can be set up prior to final installation

DIN rail panel mountable

The Elexant 650c-Modbus is equipped with a RS485 port for Modbus communication to a BMS system which can be used for configuration, monitoring and alarm purposes

Ice rain feature - preheating the surface to prevent the issue of freezing rain (for surface snow melting application only)

# **SPECIFICATIONS**

Table 1/3							
Catalog Number	Item Name	Alarm Relay	Communication	Communication s Protocol	Depth	Hazardous Area	
1244-022835	Elexant 650c- Modbus	Yes	Yes	Modbus RTU	155 mm	No	

Table 2/3							
Catalog Number	Item Name	Height	IP Rating	Mounting	Output Relay	Sensor Type	
1244-022835	Elexant 650c- Modbus	110 mm	IP20	DIN Rail	2 x 4 A @ 230 VAC	NTC	

Table 3/3							
Catalog Number	Item Name	Supply Voltage	Temperature Control Range	Width			
1244-022835	Elexant 650c-Modbus	230 - 253 V	-20 to 30 °C	55 mm			

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa Tel +32.16.213.511

Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific** 

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com