

Ladder Rack Straight Sections (cULus Classified)

Data Solutions



The Ladder Rack Straight Sections support cable on straight runs. It is made of 1-1/2 inch x 3/8 inch (38 mm x 8 mm) 16 gauge tubular steel. The nominal installed length is 10 feet (3.05 m). Each section is 9 foot 11-1/2 inches (3.03 m) long with cross members welded at 9-inch (229 -mm) intervals.

FEATURES

The Ladder Rack Straight Sections support cable on straight runs

It is made of 1-1/2 inch x 3/8 inch (38 mm x 8 mm) 16 gauge tubular steel

The nominal installed length is 10 feet (3.05 m)

Each section is 9 foot 11-1/2 inches (3.03 m) long with cross members welded at 9-inch (229-mm) intervals

SPECIFICATIONS

Table 1/1										
Catalog Number	Article Number	Material	Finish	Color	Color Code	Thickness				
LSS12BLK	10026	Mild Steel	Powder Coated	Jet Black	RAL 9005	1.52mm				
LSS12G	10025	Mild Steel	Powder Coated	Gray	ANSI 61	1.52mm				
LSS12GZ	10027	Mild Steel	Zinc Plated			1.52mm				
LSS12W	29913	Mild Steel	Powder Coated	White		1.52mm				

CatalogNumber	Article Number	Material	Finish	Color	Color Code	Thickness
LSS15BLK	29983	Mild Steel	Powder Coated	Jet Black	RAL 9005	1.52mm
LSS15W	29984	Mild Steel	Powder Coated	White		1.52mm
LSS18BLK	10032	Mild Steel	Powder Coated	Jet Black	RAL 9005	1.52mm
LSS18G	10028	Mild Steel	Powder Coated	Gray	ANSI 61	1.52mm
LSS18GZ	10033	Mild Steel	Zinc Plated			1.52mm
LSS18W	29914	Mild Steel	Powder Coated	White		1.52mm
LSS24BLK	17335	Mild Steel	Powder Coated	Jet Black	RAL 9005	1.52mm
LSS24W	29915	Mild Steel	Powder Coated	White		1.52mm
LSS6BLK	10023	Mild Steel	Powder Coated	Jet Black	RAL 9005	1.52mm
LSS6G	10022	Mild Steel	Powder Coated	Gray	ANSI 61	1.52mm
LSS6GZ	10024	Mild Steel	Zinc Plated			1.52mm
LSS6W	29912	Mild Steel	Powder Coated	White		1.52mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**