

Cable Entry Gland Plate Round Locking Adapter, CCFRM



FEATURES

CCFRM Locking Adapter only; CCFRBK Frame and CCFRM Counter Nut sold separately

Halogen and silicone free component

The frames, inlays and grommets can be combined in many ways ensuring you many versatile configuration options

No need to disassemble and reconnect connectors on cables so manufactures warranty is not voided

CCFR cable entry is quick and easy to assemble

It is made of a sturdy, glass-fiber reinforced plastic

CCFG grommets needs to be ordered separately

Operating Temperature: -40 to 120 °C / -40 to 248 °F

SPECIFICATIONS

| Table 1/1 | | | | | | |
|----------------|----------------|--------|-------|-------|----------------------------|--------------|
| Catalog Number | Article Number | Height | Width | Depth | Material | Finish |
| CCFRM20A | 59669 | 38mm | 38mm | 22mm | Thermoplastic Elastomer | Smooth Matte |
| CCFRM25A | 59673 | 38mm | 38mm | 22mm | Thermoplastic Elastomer | Smooth Matte |
| CCFRM32A | 59674 | 38mm | 38mm | 22mm | Thermoplastic Elastomer | Smooth Matte |
| CCFRM40A | 59675 | 70mm | 70mm | 22mm | Thermoplastic Elastomer | Smooth Matte |
| CCFRM50A | 59676 | 70mm | 70mm | 22mm | Thermoplastic Elastomer | Smooth Matte |
| CCFRM63A | 59677 | 70mm | 70mm | 22mm | Thermoplastic Elastomer | Smooth Matte |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE