

# **AMC-1H Mechanical Thermostat**



nVent RAYCHEM AMC-1H is an ambient-sensing thermostat designed to control heat-tracing systems used for freeze protection in hazardous locations. Used to control a single heat tracing circuit or switch multiple circuits with a contactor, it has an adjustable set point.

## **FEATURES**

Simple to install and operate, single cable entry through 3/4"/19 mm NPT conduit hub

Energy saving, ambient sensing control thermostat

Adjustable set point: -15 °F to 140 °F/-9 °C to 60 °C

Electrical rating and switch: 22 A at 125/250/480 VAC, SPDT switch

Enclosure: NEMA 4, 7, 9 lacquer-coated cast aluminum housing, stainless steel hardware

Reliable during long life

## **SPECIFICATIONS**

| Table 1/2         |           |          |             |                          |                |                                      |  |  |  |
|-------------------|-----------|----------|-------------|--------------------------|----------------|--------------------------------------|--|--|--|
| Catalog<br>Number | Item Name | Material | NEMA Rating | Thermostat<br>Type       | Current Rating | Controller<br>Temperature<br>Setting |  |  |  |
| 889067-000        | AMC-1H    | Aluminum | 4, 7, 9     | Mechanical<br>Thermostat | 22 A           | -9 to 60 °C                          |  |  |  |

| Table 2/2         |           |                        |        |        |        |                             |  |  |  |
|-------------------|-----------|------------------------|--------|--------|--------|-----------------------------|--|--|--|
| Catalog<br>Number | Item Name | Max Measuring<br>Range | Height | Width  | Depth  | Area<br>Classification      |  |  |  |
| 889067-000        | AMC-1H    | 71 °C                  | 168 mm | 114 mm | 102 mm | Non-Hazardous,<br>Hazardous |  |  |  |

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com