

# IceStop Self-Regulating Heating Cable



nVent RAYCHEM IceStop self-regulating trace heating cables provide roof and gutter de-icing, suitable for all standard materials of gutters and drainpipes. Power output is 36 W/m at 0 °C in ice water, 18 W/m at 0 °C in air.

## FEATURES

Simple to design

Easy to install: cut to length, meter marks, simple fast RayClic connections

Safe and efficient in operation: no overheating, even when crossed, advanced energy saving controls

Reliable during long life: 10 year extended product warranty available, maintenance free

GM-2XT for bitumen roofs

## SPECIFICATIONS

<b>Nominal Thickness:</b>	6 mm
<b>Nominal Width:</b>	14 mm
<b>Nominal Cable Weight:</b>	130 g/m
<b>Min Installation Temperature:</b>	-18 °C
<b>Color:</b>	Black
<b>Ground Path Type:</b>	Braid
<b>Conductor Material:</b>	Nickel-Plated Copper

Table 1/1

Catalog Number	Item Name	Supply Voltage	Nominal Power Output, In Air @ 0°C, 230V	Nominal Power Output, In Ice Water @ 0°C, 230V	Outer Jacket Material
092961-000	GM-2XT	208 – 240 V	18 W/m	36 W/m	Fluoropolymer
446105-000	GM-2X	208 – 240 V	18 W/m	36 W/m	Modified Polyolefin

Catalog Number	Item Name	Supply Voltage	Nominal Power Output, In Air @ 0°C, 230V	Nominal Power Output, In Ice Water @ 0°C,230V	Outer Jacket Material
832100-000	GM-1X	120 V			Modified Polyolefin
900069-000	GM-1XT	120 V			Fluoropolymer

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

Tel +1.800.545.6258  
Fax +1.800.527.5703  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Europe, Middle East, Africa

Tel +32.16.213.511  
Fax +32.16.213.604  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Asia Pacific

Tel +86.21.2412.1688  
Fax +86.21.5426.3167  
[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

### Latin America

Tel +1.713.868.4800  
Fax +1.713.868.2333  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

Our powerful portfolio of brands:

**RAYCHEM PYROTENAX TRACER NUHEAT**