

IceStop Self-Regulating Heating Cable



nVent RAYCHEM IceStop self-regulating trace heating cables provide roof and gutter de-icing, suitable for all standard materials of gutters and drainpipes. Power output is 36 W/m at 0 °C in ice water, 18 W/m at 0 °C in air.

FEATURES

Simple to design

Easy to install: cut to length, meter marks, simple fast RayClic connections

Safe and efficient in operation: no overheating, even when crossed, advanced energy saving controls

Reliable during long life: 10 year extended product warranty available, maintenance free

GM-2XT for bitumen roofs

SPECIFICATIONS

Min Installation Temperature:	0 °F
Nominal Thickness:	0.24 in
Nominal Width:	0.54 in
Nominal Cable Weight:	92 lb/ft
Color:	Black
Ground Path Type:	Braid
Conductor Material:	Nickel-Plated Copper

Table 1/2

Catalog Number	Item Name	Supply Voltage	Nominal Power Output, In Air @ 32°F, 120V	Nominal Power Output, In Air @ 32°F, 240V	Nominal Power Output, In Ice Water @ 32°F, 120V	Nominal Power Output, In Ice Water @ 32°F, 240V
092961-000	GM-2XT	208 – 240 V		6 W/ft		12 W/ft
446105-000	GM-2X	208 – 240 V		6 W/ft		12 W/ft

CatalogNumber	Item Name	Supply Voltage	Nominal Power Output, In Air@ 32°F, 120V	Nominal Power Output, In Air@ 32°F, 240V	Nominal Power Output, In Ice Water @ 32°F, 120V	Nominal Power Output, In Ice Water @ 32°F, 240V
832100-000	GM-1X	120 V	6 W/ft		12 W/ft	
900069-000	GM-1XT	120 V	6 W/ft		12 W/ft	

Table 2/2

Catalog Number	Item Name	Outer Jacket Material
092961-000	GM-2XT	Fluoropolymer
446105-000	GM-2X	Modified Polyolefin
832100-000	GM-1X	Modified Polyolefin
900069-000	GM-1XT	Fluoropolymer

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nvent.com

Our powerful portfolio of brands:

RAYCHEM PYROTENAX TRACER NUHEAT