


RTD-7AL RTD Sensor Assembly



nVent RAYCHEM RTD-7AL is a three-wire platinum resistance temperature detector (RTD) typically used with control and monitoring systems when accurate temperature control is required. Used in CID1 locations.

FEATURES

Simple and fast to install, connection with 3/4"/19 mm NPT conduit hub

Sensor housing is NEMA-4X rated

Temperature measuring range: –100 °F to 900 °F/–73 °C to 482 °C

Reliable during long life

SPECIFICATIONS

Table 1/1

Catalog Number	Item Name	Housing Material	Mounting	Sensor Type	Max Measuring Range
RTD7AL	RTD7AL	Aluminum	Pipe Strap	PT100	900 °F

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258

Fax +1.800.527.5703

thermal.info@nvent.com

**Europe, Middle East,
Africa**

Tel +32.16.213.511

Fax +32.16.213.604

thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688

Fax +86.21.5426.3167

cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800

Fax +1.713.868.2333

thermal.info@nvent.com

Our powerful portfolio of brands:

RAYCHEM PYROTENAX TRACER NUHEAT