

RTD-CS Corrugated Sheath RTD Sensor



nVent RAYCHEM RTD-3CS, RTD-10CS and RTD50CS are three-wire platinum resistance temperature detector (RTD) typically used with monitoring and control systems when accurate temperature control is required. Used in non-hazardous and CID2 locations.

CARACTERÍSTICAS

Simple and fast to install

Direct connection to controller with 1/2"/12.7 mm NPT fitting that connects to the conduit box: allows mounting of the RTD in a typical ambient and splicing of RTD extension wire back to the controller

Sensor housing is 316 stainless steel, lead wire is heathed in Alloy 825

Temperature measuring range: -100 °F to 300 °F/-73 °C to 149 °C

Reliable during long life

ESPECIFICACIONES

Table 1/1

Número de catálogo	Material de carcasa	Rango de medición máximo	Longitud de cable
RTD10CS	Acero inoxidable, 316	204 °C	3 m

ADVERTENCIA

Los productos nVent deben instalarse y usarse solo como se indica en las hojas de instrucciones y materiales de capacitación del producto nVent. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. La instalación incorrecta, el mal uso, la aplicación incorrecta u otras fallas en el seguimiento completo de las instrucciones y advertencias de nVent pueden causar el mal funcionamiento del producto, daños a la propiedad, lesiones corporales graves y la muerte y/o anular la garantía.

North America

Tel +1.800.545.6258

Fax +1.800.527.5703

thermal.info@nvent.com

**Europe, Middle East,
Africa**

Tel +32.16.213.511

Fax +32.16.213.604

thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688

Fax +86.21.5426.3167

cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800

Fax +1.713.868.2333

thermal.info@nvent.com

Nuestra poderosa cartera de marcas:

RAYCHEM PYROTENAX TRACER NUHEAT