Life Safety Electrical Circuits



CONNECT AND PROTECT

This table shows the critical circuit to be protected, gives a summary of the relevant code requirements, and provides specific code article and clause references.

TABLE 1 CODE REFERENCES

TABLE 1 GODE REI ERENGES		
Type of Electrical Circuit	NFPA Requirements	2020 National Building Code (Canada)
Emergency Power Supply Generator to transfer switch, transfer switch to emergency distribution switch board	"be a listed electrical circuit protective system with a minimum 2-hour fire rating" NEC Article 700	"all buildings within 3.2.6" Ref 3.2.7.8(3)(b) 3.2.7.10 (1 to 11)
Firefighter's elevator	"be a listed electrical circuit protective system with a minimum 2-hour fire rating" NEC Article 700	"all buildings within 3.2.6. over 36 m in height" Ref. 3.2.6.5(6) 3.2.7.9(1)(a) 3.2.7.10 (1) "buildings designed for barrier free access – nonsprinklered"
Fire pumps	"be a listed electrical circuit protective system with a minimum 2-hour fire rating" NEC Article 695, NFPA 20	"all buildings within 3.2.6." Ref 3.2.5.18 3.2.7.10(1) NFPA 20
Pressurizing fans and smoke dampers	"be a listed electrical circuit protective system with a minimum 2-hour fire rating" NEC Article 700 NFPA 101, Life Safety Code	"all buildings within 3.2.6." Ref. 3.2.6.2(2) & (3) 3.2.7.9(1)(c) 3.2.7.10(1)
Smoke venting fans	"be a listed electrical circuit protective system with a minimum 2-hour fire rating" NEC Article 700 NFPA 101, Life Safety Code	"all buildings within 3.2.6." Ref. 3.2.6.2(3) 3.2.6.6 3.2.7.9(1)(d) 3.2.7.10(1)
Emergency power for lighting and exit signs	"for safe egress must also be sufficiently illuminated" NEC Article 700.16 NFPA 101, Life Safety Code	"all buildings within 3.2.6." Ref. 3.2.7.4(1)(a) & (b) 3.2.7.10(1) 3.4.5.1(4)
Fire alarm	"survivability notification appliance circuit a 2-hour rated cable or cable system" NEC Article 760 NFPA 101, Life Safety Code NFPA 72, National Fire Alarm Code	"all buildings within 3.2.6." Ref. 3.2.7.8(1) & (3) 3.2.7.10(1)
Voice communication and firefighter's handsets	"survivability notification appliance circuit a 2-hour rated cable or cable system" NEC Article 760 NFPA 101, Life Safety Code NFPA 72, National Fire Alarm Code	"all group B occupancies within 3.2.6." "all other buildings within 3.2.6. over 36 m in height" Ref. 3.2.6.8 Ref 3.2.7.10(1) 3.2.7.8 (1) & (3)

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nVent.com

Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nVent.com

Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nVent.com

Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nVent.com



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER