


Z-Rail for Connector, EN 60603-2, DIN 41612

Servicios públicos de energía



Z-rail for connector in accordance with EN 60603-2 (DIN 41612).

CERTIFICACIONES



CARACTERÍSTICAS

Z-rails are bolted to the subrack for connector mounting (rear horizontal rail type ST, threaded insert inserted)

For connectors to EN 60603-2 (DIN 41612)

Aluminum extrusion, anodized

ESPECIFICACIONES

Table 1/2

Número de catálogo	Rack Width	Package Quantity	Longitud	Product Family	Product Type	Works With
30822-170	8 HP	1	40.64 mm	EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO	Z-Rail	Subracks, Cases

Número de catálogo	Rack Width	Package Quantity	Longitud	Product Family	Product Type	Works With
30822-065	60 HP	1	304.8 mm	EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO	Z-Rail	Subracks, Cases
30822-047	42 HP	1	213.36 mm	EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO	Z-Rail	Subracks, Cases
30822-033	28 HP	1	142.24 mm	EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO	Z-Rail	Subracks, Cases
30822-166	4 HP	1	20.32 mm	EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO	Z-Rail	Subracks, Cases
30822-089	84 HP	1	426.72 mm	EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO	Z-Rail	Subracks, Cases

Table 2/2

Número de catálogo	Certificaciones
30822-170	
30822-065	RoHS
30822-047	RoHS
30822-033	RoHS
30822-166	RoHS

Número de catálogo	Certificaciones
30822-089	RoHS

ADDITIONAL PRODUCT DETAILS

For attaching the z-rail to the horizontal rail a threaded insert and Torx panhead screw are required; please order these separately.

ADVERTENCIA

Los productos nVent deben instalarse y usarse solo como se indica en las hojas de instrucciones y materiales de capacitación del producto nVent. Las hojas de instrucciones están disponibles en www.nvent.com y con su representante de atención al cliente de nVent. La instalación incorrecta, el mal uso, la aplicación incorrecta u otras fallas en el seguimiento completo de las instrucciones y advertencias de nVent pueden causar el mal funcionamiento del producto, daños a la propiedad, lesiones corporales graves y la muerte y/o anular la garantía.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE