

Modular Junction Box



nVent RAYCHEM JBU-100 is a modular junction box used to connect power to up to three nVent RAYCHEM BTV, QTVR, XTVR, HTV or VPL industrial parallel heating cables. Offered in two versions, customized for local installation practices. All kits are also available with a light for power indication.

FEATURES

Simple and fast to install, spacious boxes with front access, captive lid screws and robust spring type terminals for secure fixing

Part of a modular component system, providing maximum flexibilty

One range for all nVent RAYCHEM industrial parallel heating cables

Simplified design in hazardous area, integral part of system approval

Cold-applied: core sealing boot with non-curing sealant; no heat gun, no hot work permit needed

Reliable during long life: 10 year extended product warranty available, maintenance free

SPECIFICATIONS

For Ex-Zone Gas: 1, 2
Inlet Quantity: 4
Connection Clamp Quantity: 6

Max Conductor Cross Section:10 mm²For Ex-Zone Dust:21, 22Inlet Type:Cable

Material:Glass Fiber Reinforced PolymerArea Classification:Non-Hazardous; Hazardous

IP Rating: IP66
Cover Attachment: Screwed

Mounting: Wall/Support Bracket Mounted

Halogen Free: Yes

Table 1/2									
Catalog Number	Item Name	E-Number	Ambient Temperature	Height	Depth	Width			
051976-000	JBU-100-E	0431197	-55 to 56 °C	160 mm	90 mm	160 mm			
069262-000	JBU-100-L-E	0431171	-40 to 40 °C	160 mm	90 mm	160 mm			
113974-000	JBU-100-L-EP	0431181	-40 to 40 °C	160 mm	90 mm	160 mm			
243948-000	JBU-100-EP	0431170	-55 to 56 °C	160 mm	90 mm	160 mm			

Table 2/2									
Catalog Number	Item Name	E-Number	Light Indication Included	Earth Plate Included	Below Insulation				
051976-000	JBU-100-E	0431197	No	No	No				
069262-000	JBU-100-L-E	0431171	Yes	No	No				
113974-000	JBU-100-L-EP	0431181	Yes	Yes	No				
243948-000	JBU-100-EP	0431170	No	Yes	No				

ADDITIONAL PRODUCT DETAILS

Localized versions may exist with limited approvals and different part numbers. Contact your local sales representative.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com **Latin America**

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com