



Guida orizzontale, posteriore, tipo L-MZ, leggera, con guida Z, 40 CV

CODICE A CATALOGO

34560-840



Combinations of horizontal rails and side panels

	A° = can be combined.	$A^{\circ} +$ = combination: not recommended		
light + L		-	+	+
heavy + H		+	rework for flange (see connection)	rework for flange and connection for heavy anchoring
light + L		rework for light	rework for flange	-
heavy + H		+	+	-
recessed rail				
side panel				
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L	heavy + H
light + L		light + L	Chassis + L</	

La guida orizzontale, tipo leggero con MZ consente l'uso di connettori DIN. I connettori sono conformi alla norma EN 60603-2.

CERTIFICAZIONI



CARATTERISTICHE

Per il montaggio diretto di connettori conformi a EN 60603 (DIN 41612)

Con guida Z per basso carico meccanico (L-MZ)

Alluminio estruso, finitura anodizzata, superficie di contatto conduttiva

ATTRIBUTI DEL PRODOTTO

Larghezza rack: 40HP

Quantità imballaggio: 1

Fine: Anodizzato

Lunghezza: 208.28mm

Materiale: Alluminio

Famiglia di prodotti: EuropacPRO; RatiopacPRO; ARIA RatiopacPRO; CompacPRO; PropacPRO

Tipo di prodotto: Guida orizzontale

Tipo: Leggera, MZ

Funziona con: Subracks; Casi

Gross Weight: 0.071kg

INFORMAZIONI DI PRODOTTO AGGIUNTIVE

La consegna è in confezioni multiple standard. I prezzi si riferiscono a ciascun articolo.

Tenere presente che le consegne possono essere effettuate nei QSP indicati (ad esempio 5 pezzi, 10 pezzi, 50 pezzi, ecc.). Le quantità d'ordine diverse (ad esempio 2 pezzi) possono essere modificate con la quantità di consegna successiva possibile = quantità confezione standard.

AVVERTIMENTO

I prodotti nVent devono essere installati e utilizzati solo come indicato nelle schede istruzioni e nei materiali di formazione di nVent. Le schede istruzioni sono disponibili su www.nvent.com e presso il vostro rappresentante del servizio clienti nVent. Un'installazione scorretta, un uso improprio, un'applicazione errata o qualsiasi altro mancato rispetto completo delle istruzioni e degli avvertimenti di nVent può causare malfunzionamenti del prodotto, danni alla proprietà, gravi lesioni personali e morte e/o annullare la vostra garanzia.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Il nostro straordinario portafoglio di marchi:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE