

nVent CADDY Cat HP J-Hook with BC200 Beam Clamp, Swivel

Data Solutions



CERTIFICATIONS



CARACTERÍSTICAS

Easy installation to beam flanges

Rotates 360 degrees to support various directional runs of cable

Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic

Provides superior fill capacity and load rating over most other non-continuous cable support alternatives

Rounded edges on J-Hooks provide proper bend radius support for high performance data cables

Cost effective alternative to expensive cable tray

Complies with EN 50174-2

Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569

ESPECIFICAÇÕES

Acabamento: Pregalvanized; Electrogalvanized

Material: Aço

Table 1/2

Número de catálogo	Número do artigo	Diâmetro (Ø)	Area	Cable Capacity, Cat 5e	Cable Capacity, Cat 6	Cable Capacity, Cat 6A
CAT16HPBC200B	181017	25mm	690mm ²	20	15	10
CAT21HPBC200B	181246	33.3mm	1174mm ²	50	40	25
CAT32HPBC200B	181018	50mm	2561mm ²	90	60	35
CAT48HPBC200B	181237	75mm	5974mm ²	200	150	80
CAT64HPBC200B	181019	100mm	9987mm ²	330	220	140

Table 2/2

Número de catálogo	Número do artigo	Espessura do flange (FT)	Static Load
CAT16HPBC200B	181017	16mm max	270N
CAT21HPBC200B	181246	16mm max	270N
CAT32HPBC200B	181018	16mm max	270N
CAT48HPBC200B	181237	16mm max	270N
CAT64HPBC200B	181019	16mm max	270N


DETALHES ADICIONAIS DO PRODUTO

Setscrew must be tightened and torqued onto the sloped side of the I-beam.

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.

Cable capacity is calculated based on a 70% fill rate.

DIAGRAMAS



AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.



O nosso forte portefólio de marcas:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE