

nVent ERIFLEX FleXbus Pre-assembled Supports

The II nVent ERIFLEX Flexbus Pre-assembled Supports is III a versatile, and user-friendly solution designed to complement your Flexbus installations. This innovative system is composed of a pre-assembled support and an aluminum profile, allowing it to accommodate multiple conductor configurations. Whether you need flat or on-edge positions, side-by-side or on top, this support system can be mounted directly to cable trays or on walls and ceilings.

The FleXbus Pre-assembled Supports are pre-mounted, guaranteeing substantial time savings during installation. By opting for these ready-to-go supports, you can reduce the total installation time for a FleXbus connection by approximately 20%.

This version of the FleXbus Supports features a single part number, with rails pre-cut to size and all components (inserts, threaded rods, bolts, and plastic modules) already mounted on the aluminum rail. No assembly is required. Simply mount the support on a cable tray or directly to the wall or ceiling. For standard FleXbus conductor routing, using these pre-assembled brackets significantly reduces installation time, making your setup process smoother and more efficient.

Engineered for reliability and safety, the nVent ERIFLEX FleXbus Pre-assembled Supports have been short-circuit tested and provides strong mechanical resistance to electromagnetic forces. It supports various neutral systems such as 3P or 3P+N and allows for easy routing in case of phase inversion or neutral rotation.



CERTIFICATIONS







CARACTERISTICAS

Save even more installation time with FleXbus Pre-assembled Supports

Adjustable clip adapts to different conductor thicknesses with open and closed positions

Strong mechanical resistance and short-circuit tested as per IEC 61914 standards, withstanding up to 67kA rms and 147kA Peak

Suitable for 3P, 3P+N, and conductors in flat or on-edge configurations

Can be mounted on ceilings or walls

Designed to fit different types of cable trays

Can be mounted horizontally or vertically

ESPECIFICAÇÕES

1000;1500 **Insulation Voltage:**

Dielectric Strength, IEC 61439.1: 3500 VAC @ 1 min Acabamento: Electrogalvanized

Em conformidade com: IEC® 60695-2-11 (Glow Wire Test 960 °C);IEC® 61439.1;IEC® 61914

Halogen Free Rating: IEC® 60754-1 Low Smoke Rating: ISO 5659-2 Flammability Rating: UL® 94V-0 Temperatura de trabalho: -40 to 130 °C

Table 1/2						
Número de catálogo	Número do artigo	Material	Profundidade (D)	Largura (W)	Altura (H)	Tamanho do condutor
FLEXSUEDG100 T1	508604	Glass Fibre Reinforced Polyamide, Aço	78mm	375mm	176mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUEDG100 TN1	508606	Glass Fibre Reinforced Polyamide, Aço	78mm	475mm	176mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUEDG50T	508600	Glass Fibre Reinforced Polyamide, Aço	78mm	337.5mm	126mm	220 mm², 360 mm², 545 mm², 640 mm²
FLEXSUEDG50T N1	508602	Glass Fibre Reinforced Polyamide, Aço	78mm	425mm	126mm	220 mm², 360 mm², 545 mm², 640 mm²
FLEXSUFLA100 T1	508612	Glass Fibre Reinforced Polyamide, Aço	78mm	487.5mm	130mm	800 mm², 960 mm², 1280 mm², 1810 mm²

Número de catálogo	Número do artigo	Material	Profundidade (D)	Largura (W)	Altura (H)	Tamanho do condutor
FLEXSUFLA100 TN1	508614	Glass Fibre Reinforced Polyamide, Aço	78mm	625mm	130mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUFLA50T	508608	Glass Fibre Reinforced Polyamide, Aço	78mm	337.5mm	126mm	220 mm², 360 mm², 545 mm², 640 mm²
FLEXSUFLA50T N1	508610	Glass Fibre Reinforced Polyamide, Aço	78mm	425mm	126mm	220 mm ² , 360 mm ² , 545 mm ² , 640 mm ²
FLEXSUEDG100 T2	508605	Glass Fibre Reinforced Polyamide, Aço	78mm	375mm	340mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUEDG100 TN2	508607	Glass Fibre Reinforced Polyamide, Aço	78mm	475mm	340mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUEDG50T 2	508601	Glass Fibre Reinforced Polyamide, Aço	78mm	337.5mm	240mm	220 mm², 360 mm², 545 mm², 640 mm²
FLEXSUEDG50T N2	508603	Glass Fibre Reinforced Polyamide, Aço	78mm	425mm	240mm	220 mm², 360 mm², 545 mm², 640 mm²
FLEXSUFLA100 T2	508613	Glass Fibre Reinforced Polyamide, Aço	78mm	487.5mm	248mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUFLA100 TN2	508615	Glass Fibre Reinforced Polyamide, Aço	78mm	625mm	248mm	800 mm², 960 mm², 1280 mm², 1810 mm²
FLEXSUFLA50T	508609	Glass Fibre Reinforced Polyamide, Aço	78mm	337.5mm	240mm	220 mm², 360 mm², 545 mm², 640 mm²
FLEXSUFLA50T N2	508611	Glass Fibre Reinforced Polyamide, Aço	78mm	425mm	240mm	220 mm ² , 360 mm ² , 545 mm ² , 640 mm ²

Table 2/2					
Número de catálogo	Número do artigo	Número de fases	Conductor Quantity	Orientação	Peso unitário

FLEXSUEDG100T1	508604	3	1	On Edge	1.87 kg
FLEXSUEDG100TN 1	508606	3	1	On Edge	2.44 kg
FLEXSUEDG50T1	508600	3	1	On Edge	1.4 kg
FLEXSUEDG50TN1	508602	3	1	On Edge	1.77 kg
FLEXSUFLA100T1	508612	3	1	Flat	1.93 kg
FLEXSUFLA100TN 1	508614	3	1	Flat	2.49 kg
FLEXSUFLA50T1	508608	3	1	Flat	1.34 kg
FLEXSUFLA50TN1	508610	3	1	Flat	1.69 kg
FLEXSUEDG100T2	508605	3	2	On Edge	3.46 kg
FLEXSUEDG100TN 2	508607	3	2	On Edge	4.54 kg
FLEXSUEDG50T2	508601	3	2	On Edge	2.49 kg
FLEXSUEDG50TN2	508603	3	2	On Edge	3.17 kg
FLEXSUFLA100T2	508613	3	2	Flat	3.48 kg
FLEXSUFLA100TN 2	508615	3	2	Flat	4.52 kg
FLEXSUFLA50T2	508609	3	2	Flat	2.37 kg
FLEXSUFLA50TN2	508611	3	2	Flat	3.01 kg


Installation Standard: AS 3008;BS 7671;CEI 64-8;CSN;DIN VDE 0100;HD 384;IEC® 60364


DETALHES ADICIONAIS DO PRODUTO

When using a cable tray, we recommend installing a FleXbus Support at each end to protect the FleXbus Conductor from potential sharp edges.

For easier installation of the FleXbus Conductors on cable trays, we suggest using cantilever systems to provide easy and direct access during the installation phases.

DIAGRAMAS





AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.

América do Norte

+1 800 753 9221 Opção 1 – Apoio ao cliente Opção 2 – Assistência técnica

Europa

Países Baixos: +31 800-0200135 França: +33 800 901 793

Europa

Alemanha: 800 1890272 Outros países: +31 13 5835404

APAC

Xangai: + 86 21 2412 1618/19 Sydney:

+61 2 9751 8500



O nosso forte portefólio de marcas:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE