

Elexant 4010i Replacement Control Module

nVent RAYCHEM ELEXANT 4010i-MOD is a replacement module for the Elexant 4010i heat tracing controller.

FEATURES

Simple to install

Reliable during long life: 2 year product warranty available

SPECIFICATIONS

Current Alarm: 0.1 - 100 A

Autocycle: 1 - 750 h

Ground Fault Alarm: 10 - 500 mA

Ethernet: 10/100 Base-T

Max Power Supply Input Wire Size: 16.8 mm²

Max Heating Cable Output Wire Size: 16.8 mm²

Control Max Current: 32A @ 40°C, De-Rated to 24A @ 50°C and Further De-Rated to 16A @ 60°C

Max Ground Terminal Wire Size: 33.6 mm^2 Voltage Alarm: 80 - 300 V

Control Max Voltage: 277 VAC Nominal, 50/60Hz

Relative Humidity: 0% to 90%, Noncondensating

Communication Protocol: Modbus RTU; Modbus/TCP; DHCP

Control Relay Type: Double-Pole, Solid-State; Double-Pole, Mechanical

Communication: RS-485; Ethernet

Control Algorithms: On/Off, Proportional, PASC, Always On, Always Off

RS-485 Cable Type: One 2-Wire, Shielded Twisted Pair

Temperature Control Range: -200 to 700 °CTemperature Alarm: -200 to 700 °COperating Temperature: -40 to 60 °C

Catalog Number	Item Name
10380-016	4010i-MOD-IS
10380-015	4010i-MOD

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com