

Universal Busbar Support with Neutral Circuit, **High Ampacity**



CERTIFICATIONS







FEATURES

Universal fixing system

Installs quickly and easily

Extremely robust construction

Screws are made from non-magnetic stainless steel

Halogen free insulators

SPECIFICATIONS

Max Working Voltage, IEC (Ui): 1000;1500


Complies With: IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)

Flammability Rating: UL® 94V-0 -40 to 130 °C **Working Temperature:**

Table 1/2							
Catalog Number	Article Number	Material	Typical Application Current Rating	Busbars per Phase	Busbar Width	Busbar Thickness	
UBS2-10TN-160	561870	Сталь, Glass Fibre Reinforced Polyamide	5700 A	1 - 2	160 mm	10 mm	
UBS2-10TN-200	561880	Сталь, Glass Fibre Reinforced Polyamide	5700 A	1 - 2	200 mm	10 mm	
UBS3-10TN-160	561540	Сталь, Glass Fibre Reinforced Polyamide	6200 A	1 - 3	160 mm	10 mm	
UBS1-10TN-160	561500	Сталь, Glass Fibre Reinforced Polyamide	3500 A	1	160 mm	10 mm	

Table 2/2						
Catalog Number	Article Number	Width (W)	A			
UBS2-10TN-160	561870	480 mm	110 mm			
UBS2-10TN-200	561880	480 mm	110 mm			
UBS3-10TN-160	561540	480 mm	110 mm			
UBS1-10TN-160	561500	300 mm	70 mm			

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE