



Ward Judson, Ph.D.
Engineering Manager, Labs and
Product Certifications
nVent
34600 Solon Road
Solon, OH 44139 USA
Tel +1.440.528.3788
nVent.com

November 15, 2020

Dear nVent ERICO customer:

The purpose of this letter is to verify that part numbers in the attached list are UL Listed to ANSI/UL 96.

The LPS273CTO is constructed of a similar material, but is not eligible for UL Listing because the ANSI/UL 96 standard does not define requirements for this type of component.

LPC477, LPP899xx, ISOFRP3M, and ISOCAP50 are not eligible for UL Listing because the ANSI/UL standard does not define requirements for this type of product.

For this particular product category, UL's historical practice is not to specify individual part numbers in the online listing directory.

Regards,

A handwritten signature in black ink that reads "Ward Judson". The signature is written in a cursive, flowing style.

Ward Judson

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|--|
| LPAW50T | | Y-Splice Connector, 50 mm ² , LPC050IN |
| LPAW70T | | Y-Splice Connector, 70 mm ² , LPA103IN, LPC103IN |
| LPC134250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 250' (76.2 m), 133.12 kcmil (67.424 mm ²) |
| LPC122250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 250' (76.2 m), 65.6 kcmil (33.24 mm ²) |
| LPC122500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 500' (152.4 m), 65.6 kcmil (33.24 mm ²) |
| D/SMKIVSS | 702085 | Dynasphere Air Terminal, MKIV |
| DSGOLDMK3 | 702080 | Dynasphere Air Terminal, MK3 |
| INTMKIVSS | 702089 | nVent ERICO System 3000 Interceptor |
| LPA100250 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 250' (76.2 m), 98.64 kcmil (49.98 mm ²) |
| LPA100500 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 500' (152.4 m), 98.64 kcmil (49.98 mm ²) |
| LPA100CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 98.64 kcmil (49.98 mm ²) |
| LPA101500 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 500' (152.4 m), 106.86 kcmil (54.15 mm ²) |
| LPA101CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 106.86 kcmil (54.15 mm ²) |
| LPA102500 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 500' (152.4 m), 115.08 kcmil (58.31 mm ²) |
| LPA102CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 115.08 kcmil (58.31 mm ²) |
| LPA103IN | | Insulated Conductor for Wind Turbine Blade Protection, 70 mm ² Stranded |
| LPA103IN0100.0 | | Insulated Conductor for Wind Turbine Blade Protection, 328.08' (100 m), 70 mm ² Stranded |
| LPA103IN0500.0 | | Insulated Conductor for Wind Turbine Blade Protection, 1,640.42' (500 m), 70 mm ² Stranded |
| LPA105250 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Concentric, 250' (76.2 m), 211 kcmil (106.91 mm ²) |
| LPA105500 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Concentric, 500' (152.4 m), 211 kcmil (106.91 mm ²) |
| LPA105CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Concentric, 211 kcmil (106.91 mm ²) |
| LPA140500 | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 500' (152.4 m), 41.1 kcmil (20.83 mm ²) |
| LPA140CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Aluminum, Smooth Weave, 41.1 kcmil (20.83 mm ²) |
| LPA141250 | | Non-Insulated Solid Conductor, Aluminum, Bare, #4 Solid, 250' (76.2 m) |
| LPA141500 | | Non-Insulated Solid Conductor, Aluminum, Bare, #4 Solid, 500' (152.4 m) |
| LPA141CTO | | Non-Insulated Solid Conductor, Aluminum, Bare, #4 Solid |
| LPA221 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 10" (254 mm), 1/2 UNC Thread |
| LPA221ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 10" (254 mm), 1/2 UNC Thread |
| LPA222 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 12" (304.8 mm), 1/2 UNC Thread |
| LPA222ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 12" (304.8 mm), 1/2 UNC Thread |
| LPA223 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 15" (381 mm), 1/2 UNC Thread |
| LPA223ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 15" (381 mm), 1/2 UNC Thread |
| LPA224 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 18" (457.2 mm), 1/2 UNC Thread |
| LPA224ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 18" (457.2 mm), 1/2 UNC Thread |
| LPA225 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 24" (609.6 mm), 1/2 UNC Thread |
| LPA225ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 24" (609.6 mm), 1/2 UNC Thread |
| LPA226 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 30" (762 mm), 1/2 UNC Thread |
| LPA226ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 30" (762 mm), 1/2 UNC Thread |
| LPA227 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 36" (914.4 mm), 1/2 UNC Thread |
| LPA227ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 36" (914.4 mm), 1/2 UNC Thread |
| LPA228 | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Sharp, 48" (1,219.2 mm), 1/2 UNC Thread |
| LPA228ST | | Air Terminal, Imperial Thread, Aluminum, 1/2" (12.7 mm) dia, Blunt, 48" (1,219.2 mm), 1/2 UNC Thread |
| LPA241 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 10" (254 mm), 5/8 UNC Thread |
| LPA241ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 10" (254 mm), 5/8 UNC Thread |
| LPA242 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 12" (304.8 mm), 5/8 UNC Thread |
| LPA242ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 12" (304.8 mm), 5/8 UNC Thread |
| LPA243 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 15" (381 mm), 5/8 UNC Thread |
| LPA243ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 15" (381 mm), 5/8 UNC Thread |
| LPA244 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 18" (457.2 mm), 5/8 UNC Thread |
| LPA244ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 18" (457.2 mm), 5/8 UNC Thread |
| LPA245 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPA245ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 24" (609.6 mm), 5/8 UNC Thread |
| LPA246 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 30" (762 mm), 5/8 UNC Thread |
| LPA246ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 30" (762 mm), 5/8 UNC Thread |
| LPA247 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 36" (914.4 mm), 5/8 UNC Thread |
| LPA247ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 36" (914.4 mm), 5/8 UNC Thread |
| LPA248 | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPA248ST | | Air Terminal, Imperial Thread, Aluminum, 5/8" (15.9 mm) dia, Blunt, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPA252 | | Air Terminal, Tubular with Contact Pad, Aluminum, 12" (304.8 mm) |
| LPA254 | | Air Terminal, Tubular with Contact Pad, Aluminum, 18" (457.2 mm) |
| LPA255 | | Air Terminal, Tubular with Contact Pad, Aluminum, 24" (609.6 mm) |
| LPA262 | | Air Terminal, Tubular, Imperial Thread, Aluminum, 12" (304.8 mm) |
| LPA263 | | Air Terminal, Tubular, Imperial Thread |
| LPA264 | | Air Terminal, Tubular, Imperial Thread, Aluminum, 18" (457.2 mm) |
| LPA265 | | Air Terminal, Tubular, Imperial Thread, Aluminum, 24" (609.6 mm) |
| LPA272CTO | | Extension Rod, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA273CTO | | Extension Rod, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA27512 | | Spring Point Adaptor, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA27558 | | Spring Point Adaptor, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA27812 | | Safety Ball Attachment, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA27858 | | Safety Ball Attachment, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA2832F2F | | Female-Female Swivel Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 1/2 UNC |
| LPA2832F2M | | Female-Male Swivel Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 1/2 UNC |
| LPA2842F5F | | Female-Female Swivel Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 5/8 UNC |
| LPA2842F5M | | Female-Male Swivel Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 5/8 UNC |
| LPA2845F2M | | Female-Male Swivel Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 1/2 UNC |
| LPA2855F5F | | Female-Female Swivel Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 5/8 UNC |
| LPA2855F5M | | Female-Male Swivel Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 5/8 UNC |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|---|
| LPA2932F2F | | Female-Female Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 1/2 UNC |
| LPA2932F2M | | Female-Male Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 1/2 UNC |
| LPA2932M2M | | Male-Male Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 1/2 UNC |
| LPA2942F5F | | Female-Female Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 5/8 UNC |
| LPA2942F5M | | Female-Male Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 5/8 UNC |
| LPA2942M5M | | Male-Male Adaptor, Imperial Thread, Aluminum, 1/2 UNC, 5/8 UNC |
| LPA2945F2M | | Female-Male Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 1/2 UNC |
| LPA2955F5F | | Female-Female Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 5/8 UNC |
| LPA2955F5M | | Female-Male Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 5/8 UNC |
| LPA2955M5M | | Male-Male Adaptor, Imperial Thread, Aluminum, 5/8 UNC, 5/8 UNC |
| LPA29612 | | Right Angle Extension Adaptor, Aluminum, 1/2 UNC, 1/2 UNC |
| LPA29658 | | Right Angle Extension Adaptor, Aluminum, 5/8 UNC, 5/8 UNC |
| LPA30212 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Aluminum, 1/2 UNC Thread, Flat |
| LPA30212V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Aluminum, 1/2 UNC Thread, Vertical |
| LPA30258 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Aluminum, 5/8 UNC Thread, Flat |
| LPA30258V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Aluminum, 5/8 UNC Thread, Vertical |
| LPA30412 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA30458 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA30512 | | Air Terminal Base, Imperial Thread, Aluminum, Bare, 1/2 UNC Thread, Horizontal or Vertical |
| LPA30512THRU | | Air Terminal Base, Imperial Thread, Aluminum, Bare, 1/2 UNC Thread, Horizontal or Vertical |
| LPA30558H | | Air Terminal Base, Imperial Thread, Aluminum, Bare, 5/8 UNC Thread, Horizontal |
| LPA30558THRU | | Air Terminal Base, Imperial Thread, Aluminum, Bare, 5/8 UNC Thread, Horizontal |
| LPA30558V | | Air Terminal Base, Imperial Thread, Aluminum, Bare, 5/8 UNC Thread, Vertical |
| LPA30912 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA30958 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA31212 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Aluminum, 1/2 UNC Thread, 12" (304.8 mm) |
| LPA31258 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Aluminum, 5/8 UNC Thread, 12" (304.8 mm) |
| LPA31512 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Aluminum, 1/2 UNC Thread, 8" (203.2 mm) |
| LPA31558 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Aluminum, 5/8 UNC Thread, 8" (203.2 mm) |
| LPA31812 | | Air Terminal Base, Vertical Mount, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA31858 | | Air Terminal Base, Vertical Mount, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA31912 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Aluminum, Bare, 1/2 UNC Thread |
| LPA31958 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Aluminum, Bare, 5/8 UNC Thread |
| LPA32112 | | Air Terminal Base, In-line, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA32158 | | Air Terminal Base, In-line, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA330 | | Cable/Point Pipe Support, Aluminum, Bare, 1.4"-1.75" (35.6-44.5 mm) OD |
| LPA331 | | Cable/Point Pipe Support, Aluminum, Bare, 1.75"-2.5" (44.5-63.5 mm) OD |
| LPA33912 | | Cone Air Terminal Base, Aluminum, 1/2 UNC Thread |
| LPA33958 | | Cone Air Terminal Base, Aluminum, 5/8 UNC Thread |
| LPA34012 | | Air Terminal Base, Horizontal Bond, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA34058 | | Air Terminal Base, Horizontal Bond, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA34512 | | Air Terminal Base, Ridge Mount, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA34558 | | Air Terminal Base, Ridge Mount, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA34712 | | Air Terminal Base, Sloped Roof, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA34758 | | Air Terminal Base, Sloped Roof, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA34812 | | Air Terminal Base, Standing Seam, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA34858 | | Air Terminal Base, Standing Seam, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA34912 | | Air Terminal Base, Bracket Mount, Aluminum, 1/2 UNC Thread |
| LPA34958 | | Air Terminal Base, Bracket Mount, Aluminum, 5/8 UNC Thread |
| LPA37112 | | Air Terminal Base, Pipe Mount, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA37158 | | Air Terminal Base, Pipe Mount, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA37212 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Aluminum, 1/2 UNC Thread |
| LPA37258 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Aluminum, 5/8 UNC Thread |
| LPA501 | | Stamped Crimp Cable T-Connector, Aluminum |
| LPA502 | | Stamped Bolted Parallel Cable Connector, Aluminum |
| LPA503 | | Stamped Crimp In-Line Cable Connector, Aluminum, Bare |
| LPA505 | | Stamped Crimp Parallel Cable Connector, Aluminum |
| LPA508 | | Stamped Secondary Connector, Aluminum |
| LPA510 | | Cable T-Connector, Aluminum |
| LPA513 | | In-Line Cable Connector, Aluminum |
| LPA516 | | 516 Parallel Cable Connector, Aluminum, Bare |
| LPA517 | | 517 Parallel Cable Connector, Aluminum |
| LPA527 | | 527 Parallel Cable Connector, Aluminum |
| LPA528 | | 528 Parallel Cable Connector, Aluminum, Bare |
| LPA532 | | Bonding Plate, Aluminum |
| LPA533 | | Crimp Bonding Plate, Aluminum, 8 in ² Min (51.61 cm ² Min) Contact Area |
| LPA535 | | Crimp Bonding Plate, Aluminum, 3 in ² Min (19.35 cm ² Min) Contact Area |
| LPA536 | | Bonding Plate with Welding Plate, Aluminum |
| LPA537 | | Secondary Bonding Plate, Aluminum, Bare |
| LPA540 | | Stamped Bonding Plate, Aluminum, Bare |
| LPA55112 | | Cast Bonding Lug, Aluminum, Bare, 9/16" (14.29 mm) Hole |
| LPA55114 | | Cast Bonding Lug, Aluminum, Bare, 5/16" (7.94 mm) Hole |
| LPA55138 | | Cast Bonding Lug, Aluminum, Bare, 7/16" (11.11 mm) Hole |
| LPA55312 | | Stamped Bonding Lug, Aluminum, 1/2" (12.7 mm) Hole |
| LPA55314 | | Stamped Bonding Lug, Aluminum, 1/4" (6.35 mm) Hole |
| LPA55338 | | Stamped Bonding Lug, Aluminum, 3/8" (9.53 mm) Hole |
| LPA554 | | Stamped Beam Bonding Clamp, Aluminum, Bare |
| LPA555 | | Cast Secondary Bonding Lug, Aluminum, Bare |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|--|
| LPA557 | | Cast Two Bolt Beam Bonding Clamp, Aluminum |
| LPA559 | | Cast Beam Bonding Clamp, Aluminum, Bare |
| LPA570 | | Cast U-Bolt Pipe Clamp, Aluminum, Bare |
| LPA571 | | Notched Cast U-Bolt Pipe Clamp, Aluminum, Bare |
| LPA580 | | Cast Pipe Clamp, Aluminum, Bare |
| LPA588 | | Strap Bonding Clamp, Aluminum, Bare, 6.63"-8.63" (168.4-219.2 mm) OD |
| LPA590 | | Strap Bonding Clamp, Aluminum, Bare, 8.63"-10.75" (219.2-273.1 mm) OD |
| LPA595 | | Cross-Run Cable Connector, Aluminum, Bare |
| LPA5962 | | Stamped U-Bolt Pipe Clamp, 90°, Aluminum, S304, 1.9"-2.625" (48.3-66.7 mm) OD |
| LPA5963 | | Stamped U-Bolt Pipe Clamp, 90°, Aluminum, S304, 2.63"-3.63" (66.8-92.2 mm) OD |
| LPA5964 | | Stamped U-Bolt Pipe Clamp, Aluminum, S304, 3.9"-4.625" (99.1-108 mm) OD |
| LPA5966 | | Stamped U-Bolt Pipe Clamp, Aluminum, S304, 0.438"-6.858" (111.1-174.2 mm) OD |
| LPA598 | | Bi-Metallic Cable Connector, Aluminum, Brass, S304 |
| LPA61012 | | Through Wall/Roof Connector, Aluminum, Bare, 1/2 UNC Thread |
| LPA61058 | | Through Wall/Roof Connector, Aluminum, Bare, 5/8 UNC Thread |
| LPA619 | | Through Wall/Roof Assembly, Parallel Conductor to Parallel Conductor, Aluminum, Stainless Steel 18-8 (EN 1.4305) |
| LPA620 | | Through Wall/Roof Assembly, Parallel Conductor to Bonding Lug, Aluminum Bonding Lug, Aluminum Parallel Conductor |
| LPA621 | | Through Wall/Roof Assembly, Bonding Lug to Bonding Lug, Aluminum, Stainless Steel 18-8 (EN 1.4305), 12" (304.8 mm) Rod |
| LPA62412 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Aluminum, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPA62458 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Aluminum, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPA62612 | | Through Roof Assembly, Air Terminal to In-Line Conductor, Aluminum, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPA62812 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Aluminum, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPA62858 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Aluminum, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPA664 | | Through Roof PVC Upper Connection, Aluminum In-Line Conductor, Aluminum Parallel Conductor |
| LPA66418 | | Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor, Aluminum-Aluminum Connection, 18" (457.2 mm) Rod |
| LPA66424 | | Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor, Aluminum-Aluminum Connection, 24" (609.6 mm) Rod |
| LPA669 | | Extended Strap Cable/Point Support, Aluminum |
| LPA670 | | Strap Cable/Point Support, Aluminum |
| LPA671 | | Strap Cable/Point to Pipe Support, Aluminum, 1.9"-2.4" (48.3-61 mm) OD |
| LPA672 | | Strap Cable/Point to Pipe Support, Aluminum, 2.375"-2.875" (60.3-73 mm) OD |
| LPA673 | | Strap Cable/Point to Pipe Support, Aluminum, 3.5"-4" (88.9-101.6 mm) OD |
| LPA674 | | Strap Cable/Point to Pipe Support, Aluminum, 4.5"-5" (114.3-127 mm) OD |
| LPA675 | | Extended Strap Cable/Point to Pipe Support, Aluminum, 1.9"-2.4" (48.3-61 mm) OD |
| LPA676 | | Extended Strap Cable/Point to Pipe Support, Aluminum, 2.375"-2.875" (60.3-73 mm) OD |
| LPA677 | | Extended Strap Cable/Point to Pipe Support, Aluminum, 3.5"-4" (88.9-101.6 mm) OD |
| LPA678 | | Extended Strap Cable/Point to Pipe Support, Aluminum, 4.5"-5" (114.3-127 mm) OD |
| LPA803 | | Single Hole Cable Strap, Aluminum, 0.469" (11.9 mm) OD |
| LPA804 | | Two Hole Cable Strap, Aluminum, 0.469" (12 mm) OD, 1/2" (12.7 mm) |
| LPA805 | | Single Hole Cable Strap, Aluminum, 0.5" (12.7 mm) OD |
| LPA806 | | Two Hole Cable Strap, Aluminum, 0.5" (12.7 mm) OD, 5/8" (15.88 mm) |
| LPA807 | | Single Hole Cable Strap, Aluminum, 1.3" (33 mm) OD |
| LPA808 | | Two Hole Cable Strap, Aluminum, 1.3" (33 mm) OD, 1 1/4" (31.75 mm) |
| LPA809 | | Adhesive Cable Fastener, Aluminum |
| LPA810 | | Stamped Adhesive Cable Fastener, Aluminum |
| LPA814 | | Standing Seam Machined Clamp, Aluminum |
| LPA858 | | Cable Clamp, Aluminum |
| LPAAR0510 | 711050 | Air Terminal, Metric Thread, Aluminum, M10 Thread, 7/16" (11.1 mm) dia, 19.685" (0.5 m) |
| LPAAR0515 | 710020 | Air Terminal, Metric Thread, Aluminum, M16 Thread, 5/8" (15.9 mm) dia, 19.685" (0.5 m) |
| LPAAR1010 | 711060 | Air Terminal, Metric Thread, Aluminum, M10 Thread, 7/16" (11.1 mm) dia, 39.37" (1 m) |
| LPAAR1015 | 711070 | Air Terminal, Metric Thread, Aluminum, M16 Thread, 5/8" (15.9 mm) dia, 39.37" (1 m) |
| LPC050IN | | Insulated Conductor for Wind Turbine Blade Protection, 50 mm² Stranded |
| LPC050IN0044.0 | | Insulated Conductor for Wind Turbine Blade Protection, 144.357' (44 m), 50 mm² Stranded |
| LPC050IN0047.0 | | Insulated Conductor for Wind Turbine Blade Protection, 154.199' (47 m), 50 mm² Stranded |
| LPC050IN0100.0 | | Insulated Conductor for Wind Turbine Blade Protection, 328.08' (100 m), 50 mm² Stranded |
| LPC103IN | | Insulated Conductor for Wind Turbine Blade Protection, 70 mm² Stranded |
| LPC103IN0060.0 | | Insulated Conductor for Wind Turbine Blade Protection, 196.85' (60 m), 70 mm² Stranded |
| LPC103IN0200.0 | | Insulated Conductor for Wind Turbine Blade Protection, 656.168' (200 m), 70 mm² Stranded |
| LPC120250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 250' (76.2 m), 59.45 kcmil (30.12 mm²) |
| LPC120500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 500' (152.4 m), 59.45 kcmil (30.12 mm²) |
| LPC120CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 59.45 kcmil (30.12 mm²) |
| LPC120L250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 250' (76.2 m), 59.45 kcmil (30.12 mm²) |
| LPC120L500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 500' (152.4 m), 59.45 kcmil (30.12 mm²) |
| LPC120LCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 59.45 kcmil (30.12 mm²) |
| LPC122CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 65.6 kcmil (33.24 mm²) |
| LPC122L250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 250' (76.2 m), 65.6 kcmil (33.24 mm²) |
| LPC122L500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 500' (152.4 m), 65.6 kcmil (33.24 mm²) |
| LPC122LCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 65.6 kcmil (33.24 mm²) |
| LPC123250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 250' (76.2 m), 73.8 kcmil (37.39 mm²) |
| LPC123500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 500' (152.4 m), 73.8 kcmil (37.39 mm²) |
| LPC123CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 73.8 kcmil (37.39 mm²) |
| LPC124250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 250' (76.2 m), 82 kcmil (41.55 mm²) |
| LPC124500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 500' (152.4 m), 82 kcmil (41.55 mm²) |
| LPC124CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 82 kcmil (41.55 mm²) |
| LPC124L500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 500' (152.4 m), 82 kcmil (41.55 mm²) |
| LPC124LCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 82 kcmil (41.55 mm²) |
| LPC125250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 250' (76.2 m), 98.64 kcmil (49.98 mm²) |
| LPC125CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 98.64 kcmil (49.98 mm²) |
| LPC126R250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 250' (76.2 m), 115.08 kcmil (58.31 mm²) |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|---|
| LPC126R500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 500' (152.4 m), 115.08 kcmil (58.31 mm ²) |
| LPC126RCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 115.08 kcmil (58.31 mm ²) |
| LPC126RL250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Ropelay, 250' (76.2 m), 115.08 kcmil (58.31 mm ²) |
| LPC126RL500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Ropelay, 500' (152.4 m), 115.08 kcmil (58.31 mm ²) |
| LPC126RLCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Ropelay, 115.08 kcmil (58.31 mm ²) |
| LPC127250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 250' (76.2 m), 132.52 kcmil (67.15 mm ²) |
| LPC127500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 500' (152.4 m), 132.52 kcmil (67.15 mm ²) |
| LPC127CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 132.52 kcmil (67.15 mm ²) |
| LPC127L250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Ropelay, 250' (76.2 m), 132.52 kcmil (67.15 mm ²) |
| LPC127LCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Smooth Weave, 132.52 kcmil (67.15 mm ²) |
| LPC128250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 250' (76.2 m), 98.64 kcmil (49.98 mm ²) |
| LPC128500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 500' (152.4 m), 98.64 kcmil (49.98 mm ²) |
| LPC128CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 98.64 kcmil (49.98 mm ²) |
| LPC136500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 500' (152.4 m), 167.8 kcmil (85.02 mm ²) |
| LPC136CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 167.8 kcmil (85.02 mm ²) |
| LPC137250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 250' (76.2 m), 211.6 kcmil (107.22 mm ²) |
| LPC137CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 211.6 kcmil (107.22 mm ²) |
| LPC137L250 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Tinned, Concentric, 250' (76.2 m), 211.6 kcmil (107.22 mm ²) |
| LPC137LCTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 211.6 kcmil (107.22 mm ²) |
| LPC150500 | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 500' (152.4 m), 28.7 kcmil (14.54 mm ²) |
| LPC150CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Smooth Weave, 28.7 kcmil (14.54 mm ²) |
| LPC151250 | | Non-Insulated Solid Conductor, Copper, Bare, #6 Solid, 250' (76.2 m) |
| LPC151CTO | | Non-Insulated Solid Conductor, Copper, Bare, #6 Solid |
| LPC154CTO | | Non-Insulated Solid Conductor, Copper, Bare, #2 Solid |
| LPC154LCTO | | Non-Insulated Solid Conductor, Copper, Tinned, #2 Solid |
| LPC201 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 10" (254 mm), 3/8 UNC Thread |
| LPC201B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 10" (254 mm), 3/8 UNC Thread |
| LPC201BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 10" (254 mm), 3/8 UNC Thread |
| LPC201L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 10" (254 mm), 3/8 UNC Thread |
| LPC201LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 10" (254 mm), 3/8 UNC Thread |
| LPC201ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 10" (254 mm), 3/8 UNC Thread |
| LPC202 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 12" (304.8 mm), 3/8 UNC Thread |
| LPC202B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 12" (304.8 mm), 3/8 UNC Thread |
| LPC202BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 12" (304.8 mm), 3/8 UNC Thread |
| LPC202L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 12" (304.8 mm), 3/8 UNC Thread |
| LPC202LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 12" (304.8 mm), 3/8 UNC Thread |
| LPC202ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 12" (304.8 mm), 3/8 UNC Thread |
| LPC203 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 15" (381 mm), 3/8 UNC Thread |
| LPC203B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 15" (381 mm), 3/8 UNC Thread |
| LPC203BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 15" (381 mm), 3/8 UNC Thread |
| LPC203L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 15" (381 mm), 3/8 UNC Thread |
| LPC203LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 15" (381 mm), 3/8 UNC Thread |
| LPC203ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 15" (381 mm), 3/8 UNC Thread |
| LPC204 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 18" (457.2 mm), 3/8 UNC Thread |
| LPC204B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 18" (457.2 mm), 3/8 UNC Thread |
| LPC204BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 18" (457.2 mm), 3/8 UNC Thread |
| LPC204L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 18" (457.2 mm), 3/8 UNC Thread |
| LPC204LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 18" (457.2 mm), 3/8 UNC Thread |
| LPC204ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 18" (457.2 mm), 3/8 UNC Thread |
| LPC205 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 24" (609.6 mm), 3/8 UNC Thread |
| LPC205B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 24" (609.6 mm), 3/8 UNC Thread |
| LPC205BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 24" (609.6 mm), 3/8 UNC Thread |
| LPC205L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 24" (609.6 mm), 3/8 UNC Thread |
| LPC205LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 24" (609.6 mm), 3/8 UNC Thread |
| LPC205ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 24" (609.6 mm), 3/8 UNC Thread |
| LPC206 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 30" (762 mm), 3/8 UNC Thread |
| LPC206B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 30" (762 mm), 3/8 UNC Thread |
| LPC206BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 30" (762 mm), 3/8 UNC Thread |
| LPC206L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 30" (762 mm), 3/8 UNC Thread |
| LPC206LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 30" (762 mm), 3/8 UNC Thread |
| LPC206ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 30" (762 mm), 3/8 UNC Thread |
| LPC207 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 36" (914.4 mm), 3/8 UNC Thread |
| LPC207B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 36" (914.4 mm), 3/8 UNC Thread |
| LPC207BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 36" (914.4 mm), 3/8 UNC Thread |
| LPC207L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 36" (914.4 mm), 3/8 UNC Thread |
| LPC207LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 36" (914.4 mm), 3/8 UNC Thread |
| LPC207ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 36" (914.4 mm), 3/8 UNC Thread |
| LPC208 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Sharp, 48" (1,219.2 mm), 3/8 UNC Thread |
| LPC208B | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Sharp, 48" (1,219.2 mm), 3/8 UNC Thread |
| LPC208BST | | Air Terminal, Imperial Thread, Copper, Bare, 3/8" (9.5 mm) dia, Blunt, 48" (1,219.2 mm), 3/8 UNC Thread |
| LPC208BSTOSCEN | | Air Terminal, Offset, Imperial Thread |
| LPC208L | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Sharp, 48" (1,219.2 mm), 3/8 UNC Thread |
| LPC208LST | | Air Terminal, Imperial Thread, Copper, Tinned, 3/8" (9.5 mm) dia, Blunt, 48" (1,219.2 mm), 3/8 UNC Thread |
| LPC208ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 3/8" (9.5 mm) dia, Blunt, 48" (1,219.2 mm), 3/8 UNC Thread |
| LPC221 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 1/2" (12.7 mm) dia, Sharp, 10" (254 mm), 1/2 UNC Thread |
| LPC221B | | Air Terminal, Imperial Thread, Copper, Bare, 1/2" (12.7 mm) dia, Sharp, 10" (254 mm), 1/2 UNC Thread |
| LPC221BST | | Air Terminal, Imperial Thread, Copper, Bare, 1/2" (12.7 mm) dia, Blunt, 10" (254 mm), 1/2 UNC Thread |
| LPC221L | | Air Terminal, Imperial Thread, Copper, Tinned, 1/2" (12.7 mm) dia, Sharp, 10" (254 mm), 1/2 UNC Thread |
| LPC138, LPC138CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 250 kcmil |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|---|
| LPC247L | | Air Terminal, Imperial Thread, Copper, Tinned, 5/8" (15.9 mm) dia, Sharp, 36" (914.4 mm), 5/8 UNC Thread |
| LPC247LST | | Air Terminal, Imperial Thread, Copper, Tinned, 5/8" (15.9 mm) dia, Blunt, 36" (914.4 mm), 5/8 UNC Thread |
| LPC247MBST | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Blunt, 39.4" (1,000.76 mm), 5/8 UNC Thread |
| LPC247ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 5/8" (15.9 mm) dia, Blunt, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC248 | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC248B | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC248BST | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Blunt, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC248L | | Air Terminal, Imperial Thread, Copper, Tinned, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC248ST | | Air Terminal, Imperial Thread, Copper, Nickel Plated, 5/8" (15.9 mm) dia, Blunt, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC252 | | Air Terminal, Tubular with Contact Pad, Copper, 12" (304.8 mm) |
| LPC254 | | Air Terminal, Tubular with Contact Pad, Copper, 18" (457.2 mm) |
| LPC255 | | Air Terminal, Tubular with Contact Pad, Copper, 24" (609.6 mm) |
| LPC262 | | Air Terminal, Tubular, Imperial Thread, Copper, 12" (304.8 mm) |
| LPC263 | | Air Terminal, Tubular, Imperial Thread, Copper, 15" (381 mm) |
| LPC264 | | Air Terminal, Tubular, Imperial Thread, Copper, 18" (457.2 mm) |
| LPC265 | | Air Terminal, Tubular, Imperial Thread, Copper, 24" (609.6 mm) |
| LPC266 | | Air Terminal, Tubular, Imperial Thread, Copper, 30" (762 mm) |
| LPC268 | | Air Terminal, Tubular, Imperial Thread, Copper, 48" (1,219.2 mm) |
| LPC271CTO | | Extension Rod, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC272CTO | | Extension Rod, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC273CTO | | Extension Rod, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC27512 | | Spring Point Adaptor, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC27558 | | Spring Point Adaptor, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC27812 | | Safety Ball Attachment, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC27838 | | Safety Ball Attachment, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC27858 | | Safety Ball Attachment, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC2813F3F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, 3/8 UNC, 3/8 UNC |
| LPC2813F3M | 701974 | Female-Male Swivel Adaptor, Imperial Thread, Copper, 3/8 UNC, 3/8 UNC |
| LPC28113F3F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, Tinned, 3/8 UNC, 3/8 UNC |
| LPC28113F3M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, Tinned, 3/8 UNC, 3/8 UNC |
| LPC2822F3M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, 1/2 UNC, 3/8 UNC |
| LPC2823F2F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, 3/8 UNC, 1/2 UNC |
| LPC2823F2M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, 3/8 UNC, 1/2 UNC |
| LPC28213F2F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, Tinned, 3/8 UNC, 1/2 UNC |
| LPC2832F2F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, 1/2 UNC, 1/2 UNC |
| LPC2832F2M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, 1/2 UNC, 1/2 UNC |
| LPC2842F5F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, 1/2 UNC, 5/8 UNC |
| LPC2842F5M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, 1/2 UNC, 5/8 UNC |
| LPC2845F2M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, 5/8 UNC, 1/2 UNC |
| LPC2853F5F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, 5/8 UNC, 5/8 UNC |
| LPC2855F5M | | Female-Male Swivel Adaptor, Imperial Thread, Copper, 5/8 UNC, 5/8 UNC |
| LPC28515F5F | | Female-Female Swivel Adaptor, Imperial Thread, Copper, Tinned, 5/8 UNC, 5/8 UNC |
| LPC2913F3F | | Female-Female Adaptor, Imperial Thread, Copper, 3/8 UNC, 3/8 UNC |
| LPC2913F3M | | Female-Male Adaptor, Imperial Thread, Copper, 3/8 UNC, 3/8 UNC |
| LPC2913M3M | | Male-Male Adaptor, Imperial Thread, Copper, 3/8 UNC, 3/8 UNC |
| LPC2922F3M | | Female-Male Adaptor, Imperial Thread, Copper, 1/2 UNC, 3/8 UNC |
| LPC2922M3M | | Male-Male Adaptor, Imperial Thread, Copper, 1/2 UNC, 3/8 UNC |
| LPC2923F2F | | Female-Female Adaptor, Imperial Thread, Copper, 3/8 UNC, 1/2 UNC |
| LPC2923F2M | | Female-Male Adaptor, Imperial Thread, Copper, 3/8 UNC, 1/2 UNC |
| LPC29213F2F | | Female-Female Adaptor, Imperial Thread, Copper, 3/8 UNC, 1/2 UNC |
| LPC2932F2F | | Female-Female Adaptor, Imperial Thread, Copper, 1/2 UNC, 1/2 UNC |
| LPC2932F2M | | Female-Male Adaptor, Imperial Thread, Copper, 1/2 UNC, 1/2 UNC |
| LPC2932M2M | | Male-Male Adaptor, Imperial Thread, Copper, 1/2 UNC, 1/2 UNC |
| LPC2942F5F | | Female-Female Adaptor, Imperial Thread, Copper, 1/2 UNC, 5/8 UNC |
| LPC2942F5M | | Female-Male Adaptor, Imperial Thread, Copper, 1/2 UNC, 5/8 UNC |
| LPC2945F2M | | Female-Male Adaptor, Imperial Thread, Copper, 5/8 UNC, 1/2 UNC |
| LPC2945M2M | | Male-Male Adaptor, Imperial Thread, Copper, 5/8 UNC, 1/2 UNC |
| LPC2955F5F | | Female-Female Adaptor, Imperial Thread, Copper, 5/8 UNC, 5/8 UNC |
| LPC2955F5M | | Female-Male Adaptor, Imperial Thread, Copper, 5/8 UNC, 5/8 UNC |
| LPC2955M5M | | Male-Male Adaptor, Imperial Thread, Copper, 5/8 UNC, 5/8 UNC |
| LPC29515F5F | | Female-Female Adaptor, Imperial Thread, Copper, Tinned, 5/8 UNC, 5/8 UNC |
| LPC29612 | | Right Angle Extension Adaptor, Copper, 1/2 UNC, 1/2 UNC |
| LPC29638 | | Right Angle Extension Adaptor, Copper, 3/8 UNC, 3/8 UNC |
| LPC29658 | | Right Angle Extension Adaptor, Copper, 5/8 UNC, 5/8 UNC |
| LPC30212 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, 1/2 UNC Thread, Flat |
| LPC30212V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, 1/2 UNC Thread, Vertical |
| LPC30238 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, 3/8 UNC Thread, Flat |
| LPC30238V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, 3/8 UNC Thread, Vertical |
| LPC30258 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, 5/8 UNC Thread, Flat |
| LPC30258V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, 5/8 UNC Thread, Vertical |
| LPC302112 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, Tinned, 1/2 UNC Thread, Flat |
| LPC302112V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, Tinned, 1/2 UNC Thread, Vertical |
| LPC302138 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, Tinned, 3/8 UNC Thread, Flat |
| LPC302138V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, Tinned, 3/8 UNC Thread, Vertical |
| LPC302158 | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, Tinned, 5/8 UNC Thread, Flat |
| LPC302158V | | Air Terminal Base, Stamped Adjustable, Imperial Thread, Bronze, Brass, Tinned, 5/8 UNC Thread, Vertical |
| LPC30412 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC30438 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Copper, 3/8 UNC Thread |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|---|
| LPC30458 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC304L12 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC304L38 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC304L58 | | Air Terminal Base, Stamped Narrow, Imperial Thread, Copper, Tinned, 5/8 UNC Thread |
| LPC30512 | | Air Terminal Base, Imperial Thread, Copper, Bare, 1/2 UNC Thread, Horizontal or Vertical |
| LPC30512THRU | | Air Terminal Base, Imperial Thread, Copper, Bare, 1/2 UNC Thread, Horizontal or Vertical |
| LPC30538 | | Air Terminal Base, Imperial Thread, Copper, Bare, 3/8 UNC Thread, Horizontal or Vertical |
| LPC30538THRU | | Air Terminal Base, Imperial Thread, Copper, Bare, 3/8 UNC Thread, Horizontal or Vertical |
| LPC30558H | | Air Terminal Base, Imperial Thread, Copper, Bare, 5/8 UNC Thread, Horizontal |
| LPC30558V | | Air Terminal Base, Imperial Thread, Copper, Bare, 5/8 UNC Thread, Vertical |
| LPC305L12 | | Air Terminal Base, Imperial Thread, Copper, Tinned, 1/2 UNC Thread, Horizontal or Vertical |
| LPC305L38 | | Air Terminal Base, Imperial Thread, Copper, Tinned, 3/8 UNC Thread, Horizontal or Vertical |
| LPC305L58H | | Air Terminal Base, Imperial Thread, Copper, Tinned, 5/8 UNC Thread, Horizontal |
| LPC305L58V | | Air Terminal Base, Imperial Thread, Copper, Tinned, 5/8 UNC Thread, Vertical |
| LPC30912 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC30938 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC30958 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC309L12 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC309L38 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC309L58 | | Air Terminal Base, Horizontal Mount, Imperial Thread, Copper, Tinned, 5/8 UNC Thread |
| LPC31212 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, 1/2 UNC Thread, 12" (304.8 mm) |
| LPC31238 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, 3/8 UNC Thread, 12" (304.8 mm) |
| LPC31258 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, 5/8 UNC Thread, 12" (304.8 mm) |
| LPC312L12 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, Tinned, 1/2 UNC Thread, 12" (304.8 mm) |
| LPC312L38 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, Tinned, 3/8 UNC Thread, 12" (304.8 mm) |
| LPC31512 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, 1/2 UNC Thread, 8" (203.2 mm) |
| LPC31538 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, 3/8 UNC Thread, 8" (203.2 mm) |
| LPC31558 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, 5/8 UNC Thread, 8" (203.2 mm) |
| LPC315L12 | | Air Terminal Base, Stamped Ridge Mount, Imperial Thread, Copper, Tinned, 1/2 UNC Thread, 8" (203.2 mm) |
| LPC31812 | | Air Terminal Base, Vertical Mount, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC31838 | | Air Terminal Base, Vertical Mount, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC31858 | | Air Terminal Base, Vertical Mount, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC318L12 | | Air Terminal Base, Vertical Mount, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC318L38 | | Air Terminal Base, Vertical Mount, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC31912 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Copper, Bare, 1/2 UNC Thread |
| LPC31938 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Copper, Bare, 3/8 UNC Thread |
| LPC31958 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Copper, Bare, 5/8 UNC Thread |
| LPC319L12 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC319L38 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC319L58 | | Air Terminal Base, Vertical Mount with Offset, Imperial Thread, Copper, Tinned, 5/8 UNC Thread |
| LPC32112 | | Air Terminal Base, In-line, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC32138 | | Air Terminal Base, In-line, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC32158 | | Air Terminal Base, In-line, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC321L12 | | Air Terminal Base, In-line, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC321L38 | | Air Terminal Base, In-line, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC330 | | Cable/Point Pipe Support, Brass, Bare, 1.4"-1.75" (35.6-44.5 mm) OD |
| LPC330L | | Cable/Point Pipe Support, Brass, Tinned, 1.4"-1.75" (35.6-44.5 mm) OD |
| LPC331 | | Cable/Point Pipe Support, Brass, Bare, 1.75"-2.5" (44.5-63.5 mm) OD |
| LPC331L | | Cable/Point Pipe Support, Brass, Tinned, 1.75"-2.5" (44.5-63.5 mm) OD |
| LPC33912 | | Cone Air Terminal Base, Copper, 1/2 UNC Thread |
| LPC33938 | | Cone Air Terminal Base, Copper, 3/8 UNC Thread |
| LPC33958 | | Cone Air Terminal Base, Copper, 5/8 UNC Thread |
| LPC34012 | | Air Terminal Base, Horizontal Bond, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC34038 | | Air Terminal Base, Horizontal Bond, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC34058 | | Air Terminal Base, Horizontal Bond, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC34512 | | Air Terminal Base, Ridge Mount, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC34538 | | Air Terminal Base, Ridge Mount, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC34558 | | Air Terminal Base, Ridge Mount, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC345L12 | | Air Terminal Base, Ridge Mount, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC345L38 | | Air Terminal Base, Ridge Mount, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC345L58 | | Air Terminal Base, Ridge Mount, Imperial Thread, Copper, Tinned, 5/8 UNC Thread |
| LPC34712 | | Air Terminal Base, Sloped Roof, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC34738 | | Air Terminal Base, Sloped Roof, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC34758 | | Air Terminal Base, Sloped Roof, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC347L12 | | Air Terminal Base, Sloped Roof, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC347L38 | | Air Terminal Base, Sloped Roof, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC34812 | | Air Terminal Base, Standing Seam, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC34838 | | Air Terminal Base, Standing Seam, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC34858 | | Air Terminal Base, Standing Seam, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC34912 | | Air Terminal Base, Bracket Mount, Copper, 1/2 UNC Thread |
| LPC34938 | | Air Terminal Base, Bracket Mount, Copper, 3/8 UNC Thread |
| LPC349L38 | | Air Terminal Base, Bracket Mount, Copper, Tinned, 3/8 UNC Thread |
| LPC37112 | | Air Terminal Base, Pipe Mount, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC37138 | | Air Terminal Base, Pipe Mount, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC37158 | | Air Terminal Base, Pipe Mount, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC371L12 | | Air Terminal Base, Pipe Mount, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC371L38 | | Air Terminal Base, Pipe Mount, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|--|
| LPC371L58 | | Air Terminal Base, Pipe Mount, Imperial Thread, Copper, Tinned, 5/8 UNC Thread |
| LPC372L12 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Copper, 1/2 UNC Thread |
| LPC37238 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Copper, 3/8 UNC Thread |
| LPC37258 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Copper, 5/8 UNC Thread |
| LPC372L12 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Copper, Tinned, 1/2 UNC Thread |
| LPC372L38 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Copper, Tinned, 3/8 UNC Thread |
| LPC372L58 | | Air Terminal Base, Pipe Mount Bonding, Imperial Thread, Copper, Tinned, 5/8 UNC Thread |
| LPC401CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Ropelay, 115.08 kcmil (58.31 mm ²) |
| LPC404CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Concentric, 211.6 kcmil (107.22 mm ²) |
| LPC415 | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPC416 | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPC417 | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPC418 | | Air Terminal, Imperial Thread, Copper, Bare, 5/8" (15.9 mm) dia, Sharp, 96" (2,438.4 mm), 5/8 UNC Thread |
| LPC421 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 18" (457.2 mm), 5/8 UNC Thread |
| LPC422 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPC423 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 36" (914.4 mm), 5/8 UNC Thread |
| LPC424 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPC425 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPC426 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPC427 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPC428 | | Air Terminal, Imperial Thread, Copper, Bare, 3/4" (19.1 mm) dia, Sharp, 96" (2,438.4 mm), 5/8 UNC Thread |
| LPC431 | | Industrial Stack Base, Horizontal Cable Run, Bare |
| LPC433 | | Industrial Stack Base, Horizontal/Vertical Cable Run, Bare |
| LPC435LG | | Industrial Stack Base with Stud, Horizontal Cable Run, Bare, 1 1/2" (38 mm) Thread Length |
| LPC435SH | | Industrial Stack Base with Stud, Horizontal Cable Run, Bare, 7/8" (22 mm) Thread Length |
| LPC436LG | | Industrial Stack Base with Stud, Horizontal/Vertical Cable Run, Bare, 1 1/2" (38 mm) Thread Length |
| LPC436SH | | Industrial Stack Base with Stud, Horizontal/Vertical Cable Run, Bare, 7/8" (22 mm) Thread Length |
| LPC437LG | | Industrial Stack Base with Stud, Cross Horizontal Cable Run, Bare, 1 1/2" (38 mm) Thread Length |
| LPC437SH | | Industrial Stack Base with Stud, Cross Horizontal Cable Run, Bare, 7/8" (22 mm) Thread Length |
| LPC441 | | Industrial Stack Parallel Cable Connector, Bare |
| LPC443 | | Industrial Stack In-Line Connector, Bare |
| LPC446 | | Industrial Stack T-Connector, Bare |
| LPC448 | | Industrial Stack Cross-Run Connector, Bare |
| LPC451 | | Industrial Stack Bonding Lug, Brass |
| LPC456 | | Handrail Air Terminal Support, Brass |
| LPC464 | | Industrial Stack Bonding Assembly, Lug to Lug, Bare, LPC401 |
| LPC46440 | | Industrial Stack Bonding Assembly, Lug to Lug, Bare, 4/0 Concentric |
| LPC465 | | Industrial Stack Bonding Assembly, Lug to Connector, Bare |
| LPC466 | | Rebar Bonding Clamp, Class 2 (4/0 Max) Conductor Size, UL, 10M Max, 29 mm Max, #9 Max |
| LPC467 | | Rebar Bonding Plate, 2/0 Stranded-4/0 Stranded |
| LPC468 | | Rebar Bonding Plate Cable Bond |
| LPC48034LG | | Industrial Stack Cable/Terminal Holder, Bare, 3/4" (19.1 mm) dia, 1 1/2" (38 mm) Thread Length |
| LPC48034SH | | Industrial Stack Cable/Terminal Holder, Bare, 3/4" (19.1 mm) dia, 7/8" (22 mm) Thread Length |
| LPC48058LG | | Industrial Stack Cable/Terminal Holder, Bare, 5/8" (15.9 mm) dia, 1 1/2" (38 mm) Thread Length |
| LPC48058SH | | Industrial Stack Cable/Terminal Holder, Bare, 5/8" (15.9 mm) dia, 7/8" (22 mm) Thread Length |
| LPC481LG | | Industrial Stack Pinch-Close Cable Fastener, Bare, 1 1/2" (38.1 mm) Screw |
| LPC481SH | | Industrial Stack Pinch-Close Cable Fastener, Bare, 7/8" (22.2 mm) Screw |
| LPC482LG | | Industrial Stack 2-Bolt Cable Fastener, Bare, 1 1/2" (38.1 mm) Screw |
| LPC482SH | | Industrial Stack 2-Bolt Cable Fastener, Bare, 7/8" (22.2 mm) Screw |
| LPC483 | | Cable to Metal Fastener, Class 1-Class 2 (4/0 Max) Conductor Size, UL |
| LPC49234 | | Industrial Stack Lay-in Terminal Holder, 0.719" (18.3 mm) dia, 0.615 lb (0.279 kg) |
| LPC49258 | | Industrial Stack Lay-in Terminal Holder, 0.594" (15 mm) dia, 0.615 lb (0.279 kg) |
| LPC501 | | Stamped Crimp Cable T-Connector, Copper |
| LPC501L | | Stamped Crimp Cable T-Connector, Copper, Tinned |
| LPC502 | | Stamped Bolted Parallel Cable Connector, Copper |
| LPC502A | | Stamped Bolted Parallel Cable Connector, Copper, Aluminum, S304 |
| LPC502L | | Stamped Bolted Parallel Cable Connector, Copper, Tinned |
| LPC503 | | Stamped Crimp In-Line Cable Connector, Copper, Bare |
| LPC503L | | Stamped Crimp In-Line Cable Connector, Copper, Tinned |
| LPC505 | | Stamped Crimp Parallel Cable Connector, Copper |
| LPC505L | | Stamped Crimp Parallel Cable Connector, Copper |
| LPC508L | | Stamped Secondary Connector, Copper, Tinned |
| LPC508LW | | Stamped Secondary Connector, Copper, Tinned |
| LPC510 | | Cable T-Connector, Copper |
| LPC510L | | Cable T-Connector, Copper, Tinned |
| LPC513 | | In-Line Cable Connector, Copper |
| LPC513L | | In-Line Cable Connector, Copper, Tinned |
| LPC516 | | 516 Parallel Cable Connector, Copper, Bare |
| LPC516A | | 516 Parallel Cable Connector, Copper, Aluminum, Stainless Steel 18-8 (EN 1.4305), Bare |
| LPC516L | | 516 Parallel Cable Connector, Copper, Tinned |
| LPC517 | | 517 Parallel Cable Connector, Copper |
| LPC517L | | 517 Parallel Cable Connector, Copper, Tinned |
| LPC527 | | 527 Parallel Cable Connector, Bronze |
| LPC528 | | 528 Parallel Cable Connector, Copper, Bare |
| LPC528L | | 528 Parallel Cable Connector, Copper, Tinned |
| LPC532 | | Bonding Plate, Brass |
| LPC532L | | Bonding Plate, Brass, Tinned |
| LPC533 | | Crimp Bonding Plate, Copper, 8 in ² Min (51.61 cm ² Min) Contact Area |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|---|
| LPC533L | | Crimp Bonding Plate, Copper, Tinned, 8 in ² Min (51.61 cm ² Min) Contact Area |
| LPC535 | | Crimp Bonding Plate, Copper, 3 in ² Min (19.35 cm ² Min) Contact Area |
| LPC535L | | Crimp Bonding Plate, Copper, Tinned, 3 in ² Min (19.35 cm ² Min) Contact Area |
| LPC536 | | Bonding Plate with Welding Plate, Brass |
| LPC537 | | Secondary Bonding Plate, Brass, Bare |
| LPC537L | | Secondary Bonding Plate, Brass, Tinned |
| LPC540 | | Stamped Bonding Plate, Copper, Bare |
| LPC540A | | Stamped Bonding Plate, Copper, Aluminum, S304, Bare |
| LPC540L | | Stamped Bonding Plate, Copper, Tinned |
| LPC55112 | | Cast Bonding Lug, Brass, Bare, 9/16" (14.29 mm) Hole |
| LPC55114 | | Cast Bonding Lug, Brass, Bare, 5/16" (7.94 mm) Hole |
| LPC55138 | | Cast Bonding Lug, Brass, Bare, 7/16" (11.11 mm) Hole |
| LPC551112 | | Cast Bonding Lug, Brass, Tinned, 9/16" (14.29 mm) Hole |
| LPC551138 | | Cast Bonding Lug, Brass, Tinned, 7/16" (11.11 mm) Hole |
| LPC55312 | | Stamped Bonding Lug, Bronze, 1/2" (12.7 mm) Hole |
| LPC55314 | | Stamped Bonding Lug, Bronze, 1/4" (6.35 mm) Hole |
| LPC55338 | | Stamped Bonding Lug, Bronze, 3/8" (9.53 mm) Hole |
| LPC553112 | | Stamped Bonding Lug, Bronze, Tinned, 1/2" (12.7 mm) Hole |
| LPC553114 | | Stamped Bonding Lug, Bronze, Tinned, 1/4" (6.35 mm) Hole |
| LPC553138 | | Stamped Bonding Lug, Bronze, Tinned, 3/8" (9.53 mm) Hole |
| LPC554 | | Stamped Beam Bonding Clamp, Copper, Bare |
| LPC554L | | Stamped Beam Bonding Clamp, Copper, Tinned |
| LPC555 | | Cast Secondary Bonding Lug, Brass, Bare |
| LPC555L | | Cast Secondary Bonding Lug, Brass, Tinned |
| LPC557 | | Cast Two Bolt Beam Bonding Clamp, Copper |
| LPC557L | | Cast Two Bolt Beam Bonding Clamp, Copper, Tinned |
| LPC559 | | Cast Beam Bonding Clamp, Copper, Bare |
| LPC559L | | Cast Beam Bonding Clamp, Copper, Tinned |
| LPC570 | | Cast U-Bolt Pipe Clamp, Brass, Bare |
| LPC570L | | Cast U-Bolt Pipe Clamp, Brass, Tinned |
| LPC571 | | Notched Cast U-Bolt Pipe Clamp, Brass, Bare |
| LPC571L | | Notched Cast U-Bolt Pipe Clamp, Brass, Tinned |
| LPC580 | | Cast Pipe Clamp, Brass, Bare |
| LPC580L | | Cast Pipe Clamp, Brass, Tinned |
| LPC588 | | Strap Bonding Clamp, Copper, Tinned, 6.63"-8.63" (168.4-219.2 mm) OD |
| LPC590 | | Strap Bonding Clamp, Copper, Tinned, 8.63"-10.75" (219.2-273.1 mm) OD |
| LPC595 | | Cross-Run Cable Connector, Brass, Bare |
| LPC595L | | Cross-Run Cable Connector, Brass, Tinned |
| LPC5962 | | Stamped U-Bolt Pipe Clamp, 90°, Copper, S304, 1.9"-2.625" (48.3-66.7 mm) OD |
| LPC5963 | | Stamped U-Bolt Pipe Clamp, 90°, Copper, S304, 2.63"-3.63" (66.8-92.2 mm) OD |
| LPC5964 | | Stamped U-Bolt Pipe Clamp, Copper, S304, 3.9"-4.625" (99.1-108 mm) OD |
| LPC5966 | | Stamped U-Bolt Pipe Clamp, Copper, S304, 0.438"-6.858" (111.1-174.2 mm) OD |
| LPC61012 | | Through Wall/Roof Connector, Bronze, Bare, 1/2 UNC Thread |
| LPC61038 | | Through Wall/Roof Connector, Bronze, Bare, 3/8 UNC Thread |
| LPC61058 | | Through Wall/Roof Connector, Bronze, Bare, 5/8 UNC Thread |
| LPC610B112 | | Through Wall/Roof Connector, Aluminum, Bronze, S304, Bare, 1/2 UNC Thread |
| LPC610B138 | | Through Wall/Roof Connector, Aluminum, Bronze, S304, Bare, 3/8 UNC Thread |
| LPC610B158 | | Through Wall/Roof Connector, Aluminum, Bronze, S304, Bare, 5/8 UNC Thread |
| LPC610L12 | | Through Wall/Roof Connector, Bronze, Tinned, 1/2 UNC Thread |
| LPC619 | | Through Wall/Roof Assembly, Parallel Conductor to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305) |
| LPC619A | | Through Wall/Roof Assembly, Parallel Conductor to Parallel Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305) |
| LPC620 | | Through Wall/Roof Assembly, Parallel Conductor to Bonding Lug, Copper Bonding Lug, Copper Parallel Conductor |
| LPC620A | | Through Wall/Roof Assembly, Parallel Conductor to Bonding Lug, Aluminum Bonding Lug, Copper Parallel Conductor |
| LPC621 | | Through Wall/Roof Assembly, Bonding Lug to Bonding Lug, Copper, Stainless Steel 18-8 (EN 1.4305), 12" (304.8 mm) Rod |
| LPC621A | | Through Wall/Roof Assembly, Bonding Lug to Bonding Lug, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 12" (304.8 mm) Rod |
| LPC622 | | Through Wall/Roof Assembly, Bonding Lug to Bonding Lug, Copper, Stainless Steel 18-8 (EN 1.4305), 6" (152.4 mm) Rod |
| LPC62412 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPC62438 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 3/8 UNC Thread |
| LPC62458 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPC624A12 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPC624A58 | | Through Roof Assembly, Air Terminal to Parallel Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPC62612 | | Through Roof Assembly, Air Terminal to In-Line Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPC62638 | | Through Roof Assembly, Air Terminal to In-Line Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 3/8 UNC Thread |
| LPC62658 | | Through Roof Assembly, Air Terminal to In-Line Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPC626A12 | | Through Roof Assembly, Air Terminal to In-Line Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPC626A58 | | Through Roof Assembly, Air Terminal to In-Line Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPC62812 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPC62838 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 3/8 UNC Thread |
| LPC62858 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Copper, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPC628A12 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 1/2 UNC Thread |
| LPC628A58 | | Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor, Aluminum, Copper, Stainless Steel 18-8 (EN 1.4305), 5/8 UNC Thread |
| LPC664 | | Through Roof PVC Upper Connection, Copper In-Line Conductor, Copper Parallel Conductor |
| LPC66418 | | Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor, Copper-Copper Connection, 18" (457.2 mm) Rod |
| LPC66424 | | Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor, Copper-Copper Connection, 24" (609.6 mm) Rod |
| LPC664A | | Through Roof PVC Upper Connection, Copper In-Line Conductor, Aluminum Parallel Conductor |
| LPC664A18 | | Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor, Aluminum-Copper Connection, 18" (457.2 mm) Rod |
| LPC664A24 | | Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor, Aluminum-Copper Connection, 24" (609.6 mm) Rod |
| LPC664BI | | Through Roof PVC Upper Connection, Copper In-Line Conductor, Bi-Metallic Parallel Conductor |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|--|
| LPC664L | | Through Roof PVC Upper Connection, Tinned Copper In-Line Conductor, Tinned Copper Parallel Conductor |
| LPC66518 | | Through Roof PVC Assembly, Parallel Conductor to In-Line Conductor, Copper In-Line Conductor, Copper Parallel Conductor, 20" (508 mm) Rod |
| LPC66518BI | | Through Roof PVC Assembly, Parallel Conductor to In-Line Conductor, Copper In-Line Conductor, Bi-Metallic Parallel Conductor, 20" (508 mm) Rod |
| LPC66524 | | Through Roof PVC Assembly, Parallel Conductor to In-Line Conductor, Copper In-Line Conductor, Copper Parallel Conductor, 26" (660.4 mm) Rod |
| LPC66524BI | | Through Roof PVC Assembly, Parallel Conductor to In-Line Conductor, Copper In-Line Conductor, Bi-Metallic Parallel Conductor, 26" (660.4 mm) Rod |
| LPC669 | | Extended Strap Cable/Point Support, Copper, Tinned |
| LPC670 | | Strap Cable/Point Support, Copper |
| LPC671 | | Strap Cable/Point to Pipe Support, Copper, Tinned, 1.9"-2.4" (48.3-61 mm) OD |
| LPC672 | | Strap Cable/Point to Pipe Support, Copper, Tinned, 2.375"-2.875" (60.3-73 mm) OD |
| LPC673 | | Strap Cable/Point to Pipe Support, Copper, Tinned, 3.5"-4" (88.9-101.6 mm) OD |
| LPC674 | | Strap Cable/Point to Pipe Support, Copper, Tinned, 4.5"-5" (114.3-127 mm) OD |
| LPC675 | | Extended Strap Cable/Point to Pipe Support, Copper, Tinned, 1.9"-2.4" (48.3-61 mm) OD |
| LPC676 | | Extended Strap Cable/Point to Pipe Support, Copper, Tinned, 2.375"-2.875" (60.3-73 mm) OD |
| LPC677 | | Extended Strap Cable/Point to Pipe Support, Copper, Tinned, 3.5"-4" (88.9-101.6 mm) OD |
| LPC678 | | Extended Strap Cable/Point to Pipe Support, Copper, Tinned, 4.5"-5" (114.3-127 mm) OD |
| LPC750 | | Copper Ground Plate with Cable Attachments, 12" x 24" (2 x 304.8 mm x 609.6 mm) |
| LPC751 | | Copper Ground Plate with Cable Attachments, 18" x 18" (2 x 457.2 mm x 457.2 mm) |
| LPC752 | | Copper Ground Plate with Cable Attachments, 36" x 36" (2 x 914.4 mm x 914.4 mm) |
| LPC753 | | Copper Ground Plate with Cable Attachments, 12" x 24" (1 x 304.8 mm x 609.6 mm) |
| LPC754 | | Copper Ground Plate with Cable Attachments, 18" x 18" (1 x 457.2 mm x 457.2 mm) |
| LPC755 | | Copper Ground Plate with Cable Attachments, 36" x 36" (1 x 914.4 mm x 914.4 mm) |
| LPC790 | | Ground Rod Clamp, Class 1-Class 2 (4/0 Max) Conductor Size, UL, 1/2"-3/4" dia |
| LPC795 | | U-Bolt Ground Rod Clamp, Class 1-Class 2 (4/0 Max) Conductor Size, UL, 1/2"-3/4" dia |
| LPC801 | | Single Hole Cable Strap, Copper, 0.469" (11.9 mm) OD |
| LPC801L | | Single Hole Cable Strap, Copper, Tinned, 0.469" (11.9 mm) OD |
| LPC802 | | Two Hole Cable Strap, Copper, 0.469" (12 mm) OD, 3/8" (9.84 mm) |
| LPC803 | | Single Hole Cable Strap, Copper, 0.469" (11.9 mm) OD |
| LPC803L | | Single Hole Cable Strap, Copper, Tinned, 0.469" (11.9 mm) OD |
| LPC804 | | Two Hole Cable Strap, Copper, 0.469" (12 mm) OD, 1/2" (12.7 mm) |
| LPC805 | | Single Hole Cable Strap, Copper, 0.5" (12.7 mm) OD |
| LPC80538 | | Single Hole Cable Strap, Copper, 0.5" (12.7 mm) OD |
| LPC805L | | Single Hole Cable Strap, Copper, Tinned, 0.5" (12.7 mm) OD |
| LPC806 | | Two Hole Cable Strap, Copper, 0.5" (12.7 mm) OD, 5/8" (15.88 mm) |
| LPC807 | | Single Hole Cable Strap, Copper, 1.3" (33 mm) OD |
| LPC807L | | Single Hole Cable Strap, Copper, Tinned, 1.3" (33 mm) OD |
| LPC808 | | Two Hole Cable Strap, Copper, 1.3" (33 mm) OD, 1 1/4" (31.75 mm) |
| LPC808L | | Two Hole Cable Strap, Copper, Tinned, 1.3" (33 mm) OD, 1 1/4" (31.75 mm) |
| LPC809 | 701973 | Adhesive Cable Fastener, Copper |
| LPC809L | | Adhesive Cable Fastener, Copper, Tinned |
| LPC810 | | Stamped Adhesive Cable Fastener, Copper |
| LPC810L | | Stamped Adhesive Cable Fastener, Copper, Tinned |
| LPC814 | | Standing Seam Machined Clamp, Copper |
| LPC823 | | Tree Spike |
| LPC858 | | Cable Clamp, Brass |
| LPC858L | | Cable Clamp, Brass, Tinned |
| LPCAR0510 | 711080 | Air Terminal, Metric Thread, Copper, M10 Thread, 7/16" (11.1 mm) dia, 19.685" (0.5 m) |
| LPCAR0515 | 711090 | Air Terminal, Metric Thread, Copper, M16 Thread, 5/8" (15.9 mm) dia, 19.685" (0.5 m) |
| LPCAR1010 | 711100 | Air Terminal, Metric Thread, Copper, M10 Thread, 7/16" (11.1 mm) dia, 39.37" (1 m) |
| LPCAR1015 | 711110 | Air Terminal, Metric Thread, Copper, M16 Thread, 5/8" (15.9 mm) dia, 39.37" (1 m) |
| LPCAR2015 | 711010 | Air Terminal, Metric Thread, Copper, M16 Thread, 5/8" (15.9 mm) dia, 78.74" (2 m) |
| LPG35058 | | Galvanized Air Terminal Support, Penetrating Base, 24" Max (610 mm Max) Air Terminal Height |
| LPG35158 | | Galvanized Air Terminal Support, Penetrating Base, 30" Max (762 mm Max) Air Terminal Height |
| LPG35258 | | Galvanized Air Terminal Support, Penetrating Base, 40" Max (1,016 mm Max) Air Terminal Height |
| LPG35358 | | Galvanized Air Terminal Support, Penetrating Base, 60" Max (1,524 mm Max) Air Terminal Height |
| LPG35458 | | Galvanized Air Terminal Support, Penetrating Base, 84" Max (2,134 mm Max) Air Terminal Height |
| LPG36058 | | Galvanized Air Terminal Support, Non-Penetrating Base, 24" Max (610 mm Max) Air Terminal Height |
| LPG36158 | | Galvanized Air Terminal Support, Non-Penetrating Base, 30" Max (762 mm Max) Air Terminal Height |
| LPG36258 | | Galvanized Air Terminal Support, Non-Penetrating Base, 40" Max (1,016 mm Max) Air Terminal Height |
| LPG36358 | | Galvanized Air Terminal Support, Non-Penetrating Base, 60" Max (1,524 mm Max) Air Terminal Height |
| LPG36458 | | Galvanized Air Terminal Support, Non-Penetrating Base, 84" Max (2,134 mm Max) Air Terminal Height |
| LPLC401CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Lead Covered, Concentric, 115.08 kcmil (58.31 mm ²) |
| LPLC404CTO | | Non-Insulated Stranded Conductor for Lightning Protection, Copper, Lead Covered, Concentric, 211.6 kcmil (107.22 mm ²) |
| LPLC411 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 18" (457.2 mm), 5/8 UNC Thread |
| LPLC412 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPLC413 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 36" (914.4 mm), 5/8 UNC Thread |
| LPLC414 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPLC415 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPLC416 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPLC417 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPLC418 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 5/8" (15.9 mm) dia, Sharp, 96" (2,438.4 mm), 5/8 UNC Thread |
| LPLC422 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 3/4" (19.1 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPLC425 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 3/4" (19.1 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPLC426 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 3/4" (19.1 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPLC427 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 3/4" (19.1 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPLC428 | | Air Terminal, Imperial Thread, Copper, Lead Covered, 3/4" (19.1 mm) dia, Sharp, 96" (2,438.4 mm), 5/8 UNC Thread |
| LPLC431 | | Industrial Stack Base, Horizontal Cable Run, Lead Covered |
| LPLC433 | | Industrial Stack Base, Horizontal/Vertical Cable Run, Lead Covered |
| LPLC435LG | | Industrial Stack Base with Stud, Horizontal Cable Run, Lead Covered, 1 1/2" (38 mm) Thread Length |

| Global Part Number | Article Number | Global Description |
|--------------------|----------------|--|
| LPLC435SH | | Industrial Stack Base with Stud, Horizontal Cable Run, Lead Covered, 7/8" (22 mm) Thread Length |
| LPLC436LG | | Industrial Stack Base with Stud, Horizontal/Vertical Cable Run, Lead Covered, 1 1/2" (38 mm) Thread Length |
| LPLC436SH | | Industrial Stack Base with Stud, Horizontal/Vertical Cable Run, Lead Covered, 7/8" (22 mm) Thread Length |
| LPLC437LG | | Industrial Stack Base with Stud, Cross Horizontal Cable Run, Lead Covered, 1 1/2" (38 mm) Thread Length |
| LPLC437SH | | Industrial Stack Base with Stud, Cross Horizontal Cable Run, Lead Covered, 7/8" (22 mm) Thread Length |
| LPLC441 | | Industrial Stack Parallel Cable Connector, Lead Covered |
| LPLC443 | | Industrial Stack In-Line Connector, Lead Covered |
| LPLC446 | | Industrial Stack T-Connector, Lead Covered |
| LPLC448 | | Industrial Stack Cross-Run Connector, Lead Covered |
| LPLC451 | | Industrial Stack Bonding Lug, Brass, Lead Covered |
| LPLC464 | | Industrial Stack Bonding Assembly, Lug to Lug, Lead Covered, LPC401 |
| LPLC46440 | | Industrial Stack Bonding Assembly, Lug to Lug, Lead Covered, 4/0 Concentric |
| LPLC465 | | Industrial Stack Bonding Assembly, Lug to Connector, Lead Covered |
| LPLC468 | | Rebar Bonding Plate Cable Bond |
| LPLC48034LG | | Industrial Stack Cable/Terminal Holder, Lead Covered, 3/4" (19.1 mm) dia, 1 1/2" (38 mm) Thread Length |
| LPLC48034SH | | Industrial Stack Cable/Terminal Holder, Lead Covered, 3/4" (19.1 mm) dia, 7/8" (22 mm) Thread Length |
| LPLC48058LG | | Industrial Stack Cable/Terminal Holder, Lead Covered, 5/8" (15.9 mm) dia, 1 1/2" (38 mm) Thread Length |
| LPLC48058SH | | Industrial Stack Cable/Terminal Holder, Lead Covered, 5/8" (15.9 mm) dia, 7/8" (22 mm) Thread Length |
| LPLC481LG | | Industrial Stack Pinch-Close Cable Fastener, Lead Covered, 1 1/2" (38.1 mm) Screw |
| LPLC481SH | | Industrial Stack Pinch-Close Cable Fastener, Lead Covered, 7/8" (22.2 mm) Screw |
| LPLC482LG | | Industrial Stack 2-Bolt Cable Fastener, Lead Covered, 1 1/2" (38.1 mm) Screw |
| LPLC482SH | | Industrial Stack 2-Bolt Cable Fastener, Lead Covered, 7/8" (22.2 mm) Screw |
| LPLC49234 | | Industrial Stack Lay-in Terminal Holder, 0.719" (18.3 mm) dia, 1.81 lb (0.821 kg) |
| LPLC49258 | | Industrial Stack Lay-in Terminal Holder, 0.594" (15 mm) dia, 1.81 lb (0.821 kg) |
| LPS222 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 12" (304.8 mm), 1/2 UNC Thread |
| LPS223 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 15" (381 mm), 1/2 UNC Thread |
| LPS224 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 18" (457.2 mm), 1/2 UNC Thread |
| LPS224ST | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Blunt, 18" (457.2 mm), 1/2 UNC Thread |
| LPS225 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 24" (609.6 mm), 1/2 UNC Thread |
| LPS225ST | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Blunt, 24" (609.6 mm), 1/2 UNC Thread |
| LPS226 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 30" (762 mm), 1/2 UNC Thread |
| LPS227 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 36" (914.4 mm), 1/2 UNC Thread |
| LPS227ST | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Blunt, 36" (914.4 mm), 1/2 UNC Thread |
| LPS228 | | Air Terminal, Imperial Thread, S304, 1/2" (12.7 mm) dia, Sharp, 48" (1,219.2 mm), 1/2 UNC Thread |
| LPS2832F2F | | Female-Female Swivel Adaptor, Imperial Thread, S304, 1/2 UNC, 1/2 UNC |
| LPS2832F2M | | Female-Male Swivel Adaptor, Imperial Thread, S304, 1/2 UNC, 1/2 UNC |
| LPS2842F5F | | Female-Female Swivel Adaptor, Imperial Thread, S304, 1/2 UNC, 5/8 UNC |
| LPS2845F2M | | Female-Male Swivel Adaptor, Imperial Thread, S304, 5/8 UNC, 1/2 UNC |
| LPS2855F5F | | Female-Female Swivel Adaptor, Imperial Thread, S304, 5/8 UNC, 5/8 UNC |
| LPS2855F5M | | Female-Male Swivel Adaptor, Imperial Thread, S304, 5/8 UNC, 5/8 UNC |
| LPS2923F2F | | Female-Female Adaptor, Imperial Thread, S304, 3/8 UNC, 1/2 UNC |
| LPS2932F2F | | Female-Female Adaptor, Imperial Thread, S304, 1/2 UNC, 1/2 UNC |
| LPS2932F2M | | Female-Male Adaptor, Imperial Thread, S304, 1/2 UNC, 1/2 UNC |
| LPS2932M2M | | Male-Male Adaptor, Imperial Thread, S304, 1/2 UNC, 1/2 UNC |
| LPS2942F5F | | Female-Female Adaptor, Imperial Thread, S304, 1/2 UNC, 5/8 UNC |
| LPS2945M2M | | Male-Male Adaptor, Imperial Thread, S304, 5/8 UNC, 1/2 UNC |
| LPS2955F5F | | Female-Female Adaptor, Imperial Thread, S304, 5/8 UNC, 5/8 UNC |
| LPS2955F5M | | Female-Male Adaptor, Imperial Thread, S304, 5/8 UNC, 5/8 UNC |
| LPS2955M5M | | Male-Male Adaptor, Imperial Thread, S304, 5/8 UNC, 5/8 UNC |
| LPS411 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 18" (457.2 mm), 5/8 UNC Thread |
| LPS412 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPS413 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 36" (914.4 mm), 5/8 UNC Thread |
| LPS414 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPS414XT316 | | Air Terminal, Imperial Thread, S316, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPS415 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPS415XT316 | | Air Terminal, Imperial Thread, S316, 5/8" (15.9 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPS416 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPS416XT316 | | Air Terminal, Imperial Thread, S316, 5/8" (15.9 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPS417 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPS417XT316 | | Air Terminal, Imperial Thread, S316, 5/8" (15.9 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPS418 | | Air Terminal, Imperial Thread, S304, 5/8" (15.9 mm) dia, Sharp, 96" (2,438.4 mm), 5/8 UNC Thread |
| LPS421 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 18" (457.2 mm), 5/8 UNC Thread |
| LPS422 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPS422XT316 | | Air Terminal, Imperial Thread, S316, 3/4" (19.1 mm) dia, Sharp, 24" (609.6 mm), 5/8 UNC Thread |
| LPS423 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 36" (914.4 mm), 5/8 UNC Thread |
| LPS424 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPS424XT316 | | Air Terminal, Imperial Thread, S316, 5/8" (15.9 mm) dia, Sharp, 48" (1,219.2 mm), 5/8 UNC Thread |
| LPS425 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 60" (1,524 mm), 5/8 UNC Thread |
| LPS426 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPS426XT316 | | Air Terminal, Imperial Thread, S316, 5/8" (15.9 mm) dia, Sharp, 72" (1,828.8 mm), 5/8 UNC Thread |
| LPS427 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 84" (2,133.6 mm), 5/8 UNC Thread |
| LPS428 | | Air Terminal, Imperial Thread, S304, 3/4" (19.1 mm) dia, Sharp, 96" (2,438.4 mm), 5/8 UNC Thread |
| LPS451 | | Industrial Stack Bonding Lug, Stainless Steel 316L (EN 1.4404) |
| LPS456 | | Handrail Air Terminal Support, S304 |
| LPS815 | 701972 | Stamped Standing Seam Clamp |
| LPSAR1015 | 711115 | Air Terminal, Metric Thread, S304, M16 Thread, 5/8" (15.9 mm) dia, 39.37" (1 m) |
| LPC756 | | Copper Ground Plate with Cable Attachments, 24" x 24" (2 x 609.6 mm x 609.6 mm) |