

Connection kits and accessories for Raychem XL-TRACE LSZH, GM-2X and HWAT self-regulating heating cables

PRODUCT OVERVIEW

The Raychem RayClic system is a simple, fast and reliable connection device developed exclusively for Raychem XL-Trace LSZH, FS-A-2X, FS-B-2X, GM-2X and HWAT self-regulating heating cables.

The easy-to-install RayClic system reduces installation time, lowering the total installed cost of the heating cable system.

Simple

- No need for special tools
- Three-step installation




Reliable

- Intuitive installation
- Rugged, waterproof, UV-resistant enclosure
- IP68
- Torx head fittings




Cost-effective

- Quick installation



POWERED CONNECTION KITS

Catalog number	Part number	Description
RayClic-CE-02 	235422-000	A RayClic-CE-02 can supply power to one heating cable. Each kit contains one RayClic-CE-02 power connection, one RayClic-E-02 end seal, one RayClic-SB-04 pipe mounting bracket and two cable ties. RayClic-CE-02 has a 1.5m power cable fitted. Weight: 0.8 kg
RayClic-PS-02 	716976-000	A RayClic-PS-02 can be used as a power connection kit for supplying power to two heating cables. Each kit contains one RayClic-PS-02 powered splice connection, two RayClic-E-02 end seals, one RayClic-SB-04 pipe mounting bracket and two cable ties. RayClic-PS-02 has a 1.5m power cable fitted. Weight: 0.9 kg
RayClic-PT-02 	636284-000	A RayClic-PT-02 can be used as a power connection kit for supplying power to three heating cables. Each kit contains one RayClic-PT-02 powered tee connection, three RayClic-E-02 end seals, one RayClic-SB-04 pipe mounting bracket and two cable ties. RayClic-PT-02 has a 1.5m power cable fitted. Weight: 0.9 kg

UNPOWERED CONNECTION KITS

Catalog number	Part number	Description
RayClc-S-02 	364855-000	Splice kits are installed as needed to connect two heating cables together at one point. Each kit contains one RayClc-S-02 splice. Weight: 0.6 kg
RayClc-T-02 	441524-000	Tee kits are installed as needed to connect three heating cables together at one point. Each kit contains one RayClc-T-02 tee connection and one RayClc-E-02 end seal. Weight: 0.9 kg
RayClc-X-02 	001013-000	RayClc-X-02 kits are installed as needed to connect four heating cables together at one point. Each kit contains one RayClc-X-02 and two RayClc-E-02 end seals. Weight: 0.9 kg

ACCESSORIES

Catalog number	Part number	Description	
RayClc-E-02 	224727-000	The RayClc-E-02 is a replacement end seal kit.	
RayClc-SB-04 	616809-000	The RayClc-SB-04 is a pipe mounting bracket for use with any RayClc connection kit. One pipe mounting bracket is included with each connection kit.	

RayClc System Specifications

Rated voltage	230Vac
Maximum circuit breaker size	20A
Maximum exposure temperature (De-energised)	65°C
Maximum ambient temperature (Energised)	40°C
Minimum installation temperature	-18°C
Enclosure rating	IP68

Applicable Products

XL-Trace LSZH: 10XL2-ZH, 15XL2-ZH, 26XL2-ZH, and 31XL2-ZH
FS-A-2X and FS-B-2X
GM-2X, GM2-XT
HWAT L, M & R

APPROVALS



DESIGN AND INSTALLATION

For proper design and installation of a RayClic connection system, use the appropriate product design guide and the installation instructions included with the connection kit.

ELECTRICAL PROTECTION

Raychem requires the use of a 30mA residual current device (RCD) to provide a maximum safety and protection from fire. All trace heating circuits should be protected by C-type circuit breaker.

Europe, Middle East, Africa, India

Tel +32 16 213 511

Fax +32 16 213 604

info@chemelex.com

chemelex
excellence is everything

Raychem Tracer Pyrotenax Nuheat